# STATE OF ARKANSAS DEPARTMENT OF FINANCE AND ADMINISTRATION OFFICE OF STATE PROCUREMENT

#### STANDARD SPECIFICATIONS FOR AUTOMOBILES AND STATION WAGONS

#### 1. SCOPE AND CLASSIFICATION:

Scope - To set forth the minimum acceptable standards in obtaining automobiles in conjunction with this specification and the requirements of this state.

Classification - Vehicles covered herein shall be of the following types and options as specified in the contract award.

TYPE ABA – (not on contract, same as Type ACA)

TYPE ACA - Four (4) Door Compact Sedan, see addendum 2, page 4

TYPE ADA - Four (4) Door Mid-Size Sedan, see addendum 3, page 5

TYPE AEA - Four (4) Door Large Sedan, see addendum 4, page 6

TYPE SAA - Four (4) Door Compact Station Wagon, see addendum 5, page 7

TYPE SBA - Four (4) Door Mid-Size Station Wagon, see addendum 6, page 8

TYPE JAA - Four (4) Door Campus Security Mid-Size or Larger Sedan, see addendum 7, page 9

TYPE KAA - Four (4) Door Mid-Size Police Sedan, see addendum 8, page 10-11

TYPE LAA - Four (4) Door Large Police Sedan, see addendum 9, page 12-13

TYPE MAA - Four (4) Door Mid to Large Size Police Sedan, V6, see addendum 10,

page 14-15

TYPE MAB – Four (4) Door Mid to Large Size Police Sedan, V8, see addendum 11,

page 16-17

#### 2. APPLICABLE DOCUMENTS:

Reference to any standard(s), specification(s), amendment(s) and/or test method(s) shall be to the current issue(s) in effect on the date of the contract award.

Interior volumes, vehicle size classification, and gasoline mileage shall conform to minimums shown in the latest edition of the <u>Fuel Economy Guide</u> published by the Environmental Protection Agency.

#### 3. REQUIREMENTS:

All vehicles furnished to the State of Arkansas shall be new and delivered as specified in the contract award. Vehicles shall be furnished with all interior, exterior trim and appointments listed by the manufacturer in printed specifications and literature as standard equipment. Vehicles shall also be equipped with any and all safety equipment required by the State of Arkansas and/or applicable Federal Regulations. Any upgrades and/or additional equipment necessitated by selection of any listed option by the ordering entity shall be included in the price, and no additional charge shall be made by the vendor.

AWARD NO: SP-09-0028 PAGE 2

<u>Warranty</u> - From date of delivery, each vehicle shall be accompanied by a warranty for a minimum of thirty six (36) months or thirty six thousand (36,000) miles, whichever comes first. Warranty shall certify that the vehicle is of good material and workmanship and that the replacement of any part or parts that fail under normal use within the designated period, free of negligence or accident, will be promptly repaired or replaced at NO cost to the agency, institution, or other public body that purchased the vehicle.

<u>Specific Requirements</u> - See addenda 1 through 11 for specific requirements appropriate to each type of vehicle listed herein.

#### 4. SAMPLING, INSPECTION AND TEST PROCEDURES:

Responsibility for Inspection - Unless otherwise specified, the successful contractor will be responsible for performing all inspections required herein. The Office of State Procurement reserves the right to make any and all inspections deemed necessary to insure compliance with this specification.

#### 5. PREPARATION FOR DELIVERY:

Each vehicle shall be completely serviced, cleaned, and thoroughly inspected by the successful contractor just prior to delivery to the purchasing entity. No dealer advertisement shall be on any vehicle purchased by the State of Arkansas.

#### PREDELIVERY REQUIREMENTS:

- a. Complete lubrication.
- b. Fill crankcase with oil.
- c. Adjustment of engine to proper operating conditions.
- d. Inflate tires to proper pressure.
- e. Careful check to assure perfect operation of all mechanical features.
- f. Front end alignment and wheels balanced.
- g. Cleaning of vehicle, if necessary, and removal of all unnecessary tags, stickers, papers, etc. Window price sticker shall not be removed.
- h. No dealer's insignia shall be affixed to vehicle.
- i. A minimum five gallons of fuel in each vehicle.
- j. Delivery shall be during normal working hours, 8 A.M. to 4 P.M., Monday through Friday.
- k. License plate holders installed, front and rear.

AWARD NO: SP-09-0028 PAGE 3

\*

#### SPECIFICATION FOR AUTOMOBILES AND STATION WAGONS

ADDENDUM 1: TYPE ABA: Four (4) Door Subcompact Sedan

#### A. Size Classification

- A.1 Vehicle shall be classified in the latest edition of the U.S. Environmental Protection Agency's <u>Fuel Economy Guide</u> as either a subcompact or larger sedan.
- B. Equipment
- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, and type recommended by manufacturer for vehicle as equipped.
  - g. Cooling System: factory installed and type recommended by manufacturer for vehicle as equipped.
  - h. Doors: minimum of four (4) side doors. Body side molding shall be included.
  - i. Engine: a gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Floor Mats: individual front and rear, color to coincide with interior.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Operator's Manual.
  - n. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - o. Power Windows and Door Locks: factory installed.
  - p. Power Brakes: factory installed.
  - g. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Rear Seat: manufacturer's standard type for vehicle.
  - t. Suspension: type recommended by manufacturer for vehicle as equipped.
  - u. Tires: four (4) radial, tubeless, tires of the size and load range recommended by vehicle manufacturer for automobile as equipped and one (1) mounted spare tire with wheel, either "space saver" or full size.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
- B.2 Optional Equipment Purchaser may choose from the following:

AWARD NO: SP-09-0028 PAGE 4

#### ADDENDUM 2: TYPE ACA- Four (4) Door Compact Sedan

#### A. Size Classification

A.1 Vehicle shall be classified in the latest edition of the U.S. Environmental Protection Agency's <u>Fuel Economy Guide</u> as either a compact or larger sedan.

#### B. <u>Equipment</u>

- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control with tilt steering wheel (may be dealer installed but of same manufacturer as vehicle).
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, and type recommended by manufacturer for vehicle as equipped.
  - g. Cooling System: Heavy duty, including heavy duty radiator, heavy duty fan, and factory installed coolant recovery system.
  - h. Doors: minimum of four (4) side doors. Body side molding shall be included.
  - i. Engine: a gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Floor Mats: individual front and rear, color to coincide with interior.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Operator's Manual.
  - n. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - o. Power Windows and Door Locks: factory installed.
  - p. Power Brakes: factory installed.
  - q. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Rear Seat: manufacturer's standard type for vehicle.
  - t. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - u. Tires: four (4) radial, tubeless, tires of the size and load range recommend by vehicle manufacturer for automobile as equipped and one (1) mounted spare tire with wheel, either "space saver" or full size.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
- B.2 Optional Equipment Purchaser may choose from the following:

AWARD NO: SP-09-0028 PAGE 5

### ADDENDUM 3: TYPE ADA- Four (4) Door Mid-Size Sedan

#### A. Size Classification

A.1 Vehicle shall be classified in the latest edition of the U.S. Environmental Protection Agency's Fuel Economy Guide as either a mid-size or larger sedan.

#### B. <u>Equipment</u>

- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, and type recommended by manufacturer for vehicle as equipped.
  - g. Cooling System: heavy duty, including heavy duty radiator, heavy duty fan, and factory installed coolant recovery system.
  - h. Doors: minimum of four (4) side doors. Body side molding shall be included.
  - i. Engine: a gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Floor Mats: individual front and rear, color to coincide with interior.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Operator's Manual.
  - n. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - o. Power Windows and Door Locks: factory installed.
  - p. Power Brakes: factory installed.
  - q. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Rear Seat: manufacturer's standard type for vehicle.
  - t. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - u. Tires: four (4) radial, tubeless, tires of the size and load range recommended by vehicle manufacturer for automobile as equipped and one (1) mounted spare tire with wheel, either "space saver" or full size.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
- B.2 Optional Equipment Purchaser may choose from the following:

AWARD NO: SP-09-0028 PAGE 6

\*

### ADDENDUM 4: TYPE AEA: Four (4) Door Large Sedan

#### A. Size Classification

A.1 Vehicle shall be classified in the latest edition of the U.S. Environmental Protection Agency's <u>Fuel Economy Guide</u> as a large sedan.

#### B. <u>Equipment</u>

- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, and type recommended by manufacturer for vehicle as equipped.
  - g. Cooling System: heavy duty, including heavy duty radiator, heavy duty fan, and factory installed coolant recovery system.
  - h. Doors: minimum of four (4) side doors. Body side molding shall be included.
  - i. Engine: a gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Floor Mats: individual front and rear, color to coincide with interior.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Operator's Manual.
  - n. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - o. Power Windows and Door Locks: factory installed.
  - p. Power Brakes: factory installed.
  - q. Power Steering, factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Rear Seat: manufacturer's standard type for vehicle.
  - t. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - u. Tires: four (4) radial, tubeless, tires of the size and load range recommended by vehicle manufacturer for automobile as equipped and one (1) spare tire with wheel, either "space saver" or full size.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
- B.2 Optional Equipment Purchaser may choose from the following:
  - CB. Gasoline engine: 8 Cylinder, a minimum of 280 CID.

AWARD NO: SP-09-0028 PAGE 7

### ADDENDUM 5: TYPE SAA- Four (4) Door Compact Station Wagon

#### A. Size Classification

A.1 Vehicle shall be classified in the latest edition of the U.S. Environmental Protection Agency's <u>Fuel Economy Guide</u> as either a compact or larger station wagon.

#### B. Equipment

- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, and type recommended by manufacturer for vehicle as equipped.
  - g. Cooling System: heavy duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - h. Doors: minimum of four (4) side doors with a station wagon type rear opening. Body side molding shall be included.
  - i. Engine: a gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Floor Mats: individual front and rear, color to coincide with interior.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Operator's Manual.
  - n. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - o. Power Windows and Door Locks: factory installed.
  - p. Power Brakes: factory installed.
  - q. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Rear Seat: manufacturer's standard type for vehicle.
  - t. Suspension: type recommended by manufacturer for vehicle as equipped.
  - u. Tires: four (4) radial, tubeless, tires of the size and load range recommended by vehicle manufacturer for automobile as equipped and one (1) mounted spare tire with wheel either "space saver" or full size.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
- B.2 Optional Equipment Purchaser may choose from the following:

AWARD NO: SP-09-0028 PAGE 8

\*

### ADDENDUM 6: TYPE SBA: Four (4) Door Mid-Size Station Wagon

#### A. Size Classification

A.1 Vehicle shall be classified in the latest edition of the U.S. Environmental Protection Agency's <u>Fuel Economy Guide</u> as either a mid-size or larger station wagon.

#### B. Equipment

- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, and type recommended by manufacturer for vehicle as equipped.
  - g. Cooling System: Heavy duty, including heavy-duty radiator, heavy duty fan, and factory installed coolant recovery system.
  - h. Doors: minimum of four (4) side doors with a station wagon type rear opening. Body side molding shall be included.
  - i. Engine: a gasoline fueled 6 cylinder engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Floor Mats: individual front and rear, color to coincide with interior.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Operator's manual.
  - n. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - o. Power Windows and Door Locks: factory installed.
  - p. Power Brakes: factory installed.
  - q. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Rear Seat: manufacturer's standard type for vehicle.
  - t. Suspension: type recommended by manufacturer for vehicle as equipped.
  - u. Tires: four (4) radial, tubeless, tires of the size and load range recommended by vehicle manufacturer for automobile as equipped and one (1) mounted spare tire with wheel, either "space saver" or full size.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
- B.2 Optional Equipment Purchaser may choose from the following:

AWARD NO: SP-09-0028 PAGE 9

ADDENDUM 7: TYPE JAA: Four (4) Door Campus Security Mid-Size or Larger Sedan

#### A. Size Classification

A.1 Vehicle shall be classified in the latest edition of the U.S. Environmental Protection Agency's <u>Fuel Economy Guide</u> as a midsize or larger car. Vehicle shall have no less than 95 or no more than 105 cubic feet of interior volume.

#### B. Equipment

- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy duty minimum of 100 amperes.
  - c. Anti-Freeze: serviced to -29°1/2C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Cooling System: heavy duty, including heavy duty radiator, heavy duty fan, and factory installed coolant recovery.
  - h. Defroster (rear window).
  - i. Disconnect door courtesy light switches.
  - j. Engine: a gasoline fueled 6 cylinder engine of the type recommended by the manufacturer for the vehicle as equipped.
  - k. Floor Mats: individual front and rear, color to coincide with interior.
  - I. Inside hood latch control.
  - m. License plate brackets, front and rear.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by the ordering entity.
  - p. Power Windows and Door Locks: factory installed.
  - q. Power Brakes: factory installed, and compatible with vehicle as equipped.
  - r. Power Steering: factory installed.
  - s. Protective Body Side Molding, factory installed.
  - t. Radio: factory installed in dash AM/FM.
  - u. Radio suppression: radio frequency interference suppression measures and devices shall be incorporated into the vehicle so that interference generated does not exceed the limits established in SAE standard J-55, entitled "Measurement of Vehicle Radio Interference" (30 to 40 megacycles).
  - v. Seats: bench and/or bucket types as recommended by manufacturer.
  - w. Suspension: type recommended by manufacturer for vehicle as equipped.
  - x. Tires: four (4) radial, tubeless, tires of the size and load range recommended by vehicle manufacturer for automobile as equipped and one (1) spare tire with wheel, either "space saver" or full size.
  - y. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
  - z. Wheels: type recommended by manufacturer for vehicle as equipped.
- B.2 Optional Equipment Purchaser may choose from the following:

AWARD NO: SP-09-0028 PAGE 10

ADDENDUM 8: TYPE KAA: Four (4) Door Mid-Size Police Sedan, (Chevrolet Impala 9C1 no substitutes)

#### A. Size Classification

A.1 Vehicle shall have no more than 105 cubic feet of passenger interior space volume and a minimum of eleven (11) cubic feet of trunk/cargo volume. Interior volumes are the ones shown as mid-size sedans in the latest Fuel Economy Guide published by the Environmental Protection Agency.

#### B. <u>Equipment</u>

- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows; tint may be dealer installed but of same manufacturer as vehicle.
  - b. Alternator: heavy duty, minimum of 100 amperes.
  - c. Anti-Freeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Brakes: ABS type brake system.
  - h. Cooling System: heavy duty, including heavy duty extra capacity radiator, heavy duty temperature controlled fan, and factory installed coolant recovery system.
  - i. Defroster (rear window).
  - j. Disconnect door courtesy light switches.
  - k. Drive Axle: manufacturer to select axle ratio which will provide the best overall performance and the heaviest duty available.
  - I. Electric Controlled Door Locks.
  - m. Engine: suitable for police pursuit work and capable of accelerating from 0 to 60 mph in a maximum of 14.5 seconds with a minimum top Speed of 105 mph as shown in the latest Michigan Police Vehicle Test. Engine shall be equipped with dual exhaust (or single if large enough for proper elimination of pressure) and external engine oil cooler.
  - n. Engine compartment light.
  - o. Floor Mats: cloth, individual front and rear, color to coincide with interior.
  - p. Glove box light.
  - q. Heater: integral fresh air heater and defroster.
  - r. Horns: dual.
  - s. Inside hood latch control.
  - t. License plate brackets; front and rear.
  - u. Lights, interior: standard dome light with map or reading lights, extra dome and reading light in center of windshield header.
  - v. Locks, Door: single key locking system for each car. Three (3) keys per vehicle.
  - w. Mirrors, Rear View: remote control both sides. Non-glare day-night inside.
  - x. Operator's Manual.
  - y. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by the ordering entity.
  - z. Police Package: including all features listed in the manufacturer's printed specifications and literature part of their police equipment package.

AWARD NO: SP-09-0028 PAGE 11

continue

ADDENDUM 8: TYPE KAA: Four (4) Door Mid-Size Police Sedan, (Chevrolet Impala 9C1 no substitutes)

- aa. Power Windows and Door Locks: factory installed.
- bb. Power Steering: firm feel power assisted steering gear and linkage.
- cc. Protective Body Side Molding; factory installed
- dd. Quiet sound group (special noise deadening insulation).
- ee. Radio: factory installed in dash AM/FM.
- ff. Radio Suppression: radio frequency interference suppression measures and devices shall be incorporated into the vehicle so that interference generated does not exceed the limits established in SAE standard J55, entitled "Measurement of Vehicle Radio Interference (30 to 40 megacycles)". gg. Remote deck lid release, control on driver's side.
- hh. Seat, Front: Bucket or Bench type recommended by manufacturer for vehicle as equipped with heavy-duty cloth upholstery.
- ii. Speedometer: 0 to 120 mph, certified calibrated within two (2) MPH. Allowable instrument error to be  $\pm$  one (1) mph at all Speeds between 10 and 100 mph.
- jj. Spotlight: factory installed, left side. not less than 5 inches with aircraft or halogen bulb.
- kk. Suspension: maximum handling package designed to limit body roll, allow flat cornering, limit drive on severe braking, limit squat on fast acceleration, and to provide optimum handling. Package should include, at a minimum, extra control front and rear shock absorbers, extra heavy duty frame or frame member reinforcement on unit frame, and front and rear stabilizer bars.
- II. Tires: Pursuit Radial, tubeless type, fabric body and belts. Tires of the size and load range recommended by vehicle manufacturer for automobile as equipped. Tires must be certified by both the tire and auto manufacturer for police use to 120 mph sustained mm. Wheels: heavy duty, 15 inch diameter.
- nn. Windshield wipers: intermittent type.
- oo. Upholstery: cloth front and vinyl rear, police duty, color to coordinate with exterior color. Dark colors and black unacceptable due to heat build-up. Includes carpet.

#### B.2 Optional Equipment - Purchaser may select the following:

- MO. Delete spotlight: spotlight may be deleted for credit.
- NO. Bucket seats.
- VM. Vinyl Floor Mats, Front & Rear
- WO. Full size wheel covers, all four wheels.
- WI. Unmarked police package: Full wheel covers, bench seats, carpeted floor, regular outside trim (also deletes spotlight)
- WL. Full sized spare with tire to match others on vehicle.
- WW. Cloth Rear Seat

AWARD NO: SP-09-0028 PAGE 12

ADDENDUM 9: TYPE LAA: Four (4) Door Large Police Pursuit Sedan, (Ford Crown Victoria no substitutes)

#### A. <u>Size Classification</u>

A.1 Vehicle shall have a minimum of 110 cubic feet of passenger interior space volume and a minimum of 20 cubic feet of trunk/cargo volume. Interior volumes are the ones shown as large sedans in the latest Fuel Economy Guide published by the Environmental Protection Agency.

#### B. <u>Equipment</u>

- B.1 Standard Equipment Every vehicle shall be equipped with the following:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows; tint may be dealer installed but of same manufacturer as vehicle.
  - b. Alternator: heavy duty, minimum of 100 amperes.
  - c. Anti-Freeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Brakes: ABS type brake system and **limited slip** rear axle.
  - h. Cooling System: heavy duty, including heavy duty extra capacity radiator, heavy duty temperature controlled fan, and factory installed coolant recovery system.
  - i. Disconnect door courtesy light switches.
  - j. Drive Axle: 3.27 axle ratio to provide the best overall performance and the heaviest duty available.
  - k. Electric Controlled Door Locks: Operable from the front only; inoperable from the rear.
  - I. Engine: suitable for police pursuit work and capable of accelerating from 0 to 60 mph in a maximum of 14.5 seconds with a minimum top Speed of 105 mph as shown in the latest Michigan Police Vehicle Test. Engine shall be 210 h.p. or larger equipped with dual exhaust (or single if large enough for proper elimination of pressure) and factory installed engine oil cooler.
  - m. Floor Mats: cloth, individual front and rear, color to coincide with interior
  - n. Warning Lights: oil pressure and coolant temperature.
  - o. Glove box light.
  - p. Heater: integral fresh air heater and defroster.
  - q. Horns, dual.
  - r. Inside hood latch control.
  - s. License plate brackets; front and rear.
  - t. Locks, Door: single key locking system for each car with three keys per vehicle.
  - u. Mirrors: rear-view with remote control, both sides. Non-glare, day-night inside.
  - v. Operator's Manual.
  - w. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by the ordering entity.
  - x. Police Package: including all features listed in manufacturer's printed specifications and literature part of police equipment package. (65A)
  - y. Power Windows and Door Locks: factory installed. **Operable from the front only;** inoperable from the rear.
  - z. Power Steering: firm feel power assisted steering gear with linkage & external oil cooler.

AWARD NO: SP-09-0028 PAGE 13

continue

ADDENDUM 9: TYPE LAA: Four (4) Door Large Police Pursuit Sedan, (Ford Crown Victoria no substitutes)

- aa. Protective Body Side Molding: factory installed
- bb. Quiet sound group (special noise deadening insulation).
- cc. Radio: factory installed in dash AM/FM.
- dd. Radio Suppression: radio frequency interference suppression measures and devices shall be incorporated into the vehicle so that generated interference does not exceed the limits established in SAE standard J55, entitled "Measurement of Vehicle Radio Interference" (30 to 40 megacycles). ee. Rear Window Defrost.
- ff. Remote deck lid release, control on driver's side.
- gg. Seats: bucket front and rear bench.
- hh. Speedometer: 0 to 120 mph, certified calibrated within two (2) mph. Allowable instrument error to be  $\pm$  one (1) mph at all Speeds between 10 and 100 mph.
- ii. Spotlight: factory installed, left side, not less than 5 inches with aircraft or halogen bulb.
- jj. Suspension: maximum handling package designed to limit body roll, allow flat cornering, limit drive on severe braking, limit squat on fast acceleration, and to provide optimum handling. Package shall include, at a minimum, extra control front and rear shock absorbers, extra heavy duty frame or frame member reinforcement on unit frame, with front and rear stabilizer bars.
- kk. Tires: P225 60 V/R x 17 tubeless, fabric body and belts. Pursuit radial tires must be certified by both the tire and auto manufacturer for police use to 120 mph sustained.
- II. Wheels: heavy duty, 16 inch diameter with metal, full wheel covers.
- mm. Windshield Wipers: intermittent type.
- nn. Upholstery: cloth front and vinyl rear, police duty, color to coordinate with exterior color.
- Dark colors and black unacceptable due to heat build-up.

#### B.2 Optional equipment - Purchaser may select the following:

#### AR. 3.55 limited slip axle ratio

#### BP. Ballistic Door Panels for driver or driver and passenger

- **DL. Daytime Running Lights**
- IO. Roof reinforcement for light bar installation.
- MO. Delete spotlight: spotlight may be deleted for credit.
- OO. Spotlight (additional, to be installed front passenger side).
- VI. Delete **limited-slip** rear axle.
- VM. Vinyl Floor Mats, Front & Rear
- WL. Full sized spare with tire to match others on vehicle
- ZI. Street Appearance Package: Chrome grill, side moldings, change police engine markings; to include front and rear cloth seats.

AWARD NO: SP-09-0028 PAGE 14

ADDENDUM 10: TYPE MAA: Four (4) Door Mid to Large Police Pursuit Sedan, 3.5L/V6 (Dodge Charger no substitutes)

#### A. Size Classification

A.1 Vehicle shall have no more than 103 cubic feet of passenger interior space volume and a minimum of 15 cubic feet of trunk/cargo volume. Interior volumes are the ones shown as mid-size sedans in the latest <u>Fuel Economy Guide</u> published by the Environmental Protection Agency.

#### B. <u>Equipment</u>

- B.1 Standard Equipment Every-vehicle shall be equipped with the following:
  - a. Air Conditioning: Manual, factory installed and manufacturer standard tinted glass in all windows, tint may be dealer installed but of same manufacturer as vehicle.
  - b. Alternator: high-output, minimum of 160 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control with tilt steering wheel (may be dealer installed, but of same manufacturer as vehicle).
  - e. Automatic Transmission: Five-Speed with overdrive.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Brakes: ABS type brake system and anti-slip rear axle.
  - h. Cooling System: Severe-duty including heavy duty extra capacity radiator, heavy duty temperature controlled fan, and factory installed coolant recovery system.
  - i. Dome Lamp: 12V LED/Incandescent.
  - j. Drive Axle: manufacturer to select axle ratio which will provide the best overall performance and the heaviest duty available.
  - k Electric Controlled Door Locks: Operable from the front only; inoperable from the rear.
  - I. Engine: 3.5-liter V 6 engine with 250 hp @ 6,400 rpm and 250 lb-ft of torque @ 3,800 rpm. Suitable for police pursuit work and capable of accelerating from 0 to 60 mph in a maximum of 14.5 seconds with a minimum top Speed of 105 mph as shown in the latest Michigan Police Vehicle Test. Engine shall be 250 horsepower or larger equipped with dual exhaust (or single if larger enough for proper elimination of pressure) and factory installed engine oil cooler.
  - m. Engine Compartment Light
  - n. External Oil Coolers: engine oil, transmission fluid, power steering fluid.
  - o. Floor Mats: cloth, individual front and rear, color to coincide with interior.
  - p. Gauge Package: Warning lamps for low oil pressure, charging system, low fuel and coolant temperature
  - g. Glove Box Light.
  - r. Heater and Defroster
  - s. Horns: Dual
  - t. Inside hood latch control
  - u. License plate brackets: front and rear
  - v. Locks, Door: single key locking system for each car with three keys per vehicle. Separate key and key fob.
  - w. Mirrors, Rearview: with remote control both sides. None-glare, day-night inside.
  - x. Operator's Manual
  - v. Under hood lamp
  - z. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by the ordering entity.

AWARD NO: SP-09-0028 PAGE 15

continue

ADDENDUM 10: TYPE MAA: Four (4) Door Mid to Large Police Pursuit Sedan, 3.5L/V6 (Dodge Charger no substitutes)

aa. Police Package: including all features listed in manufacturer's printed specifications and literature part of police equipment package.

bb. Power Window and Door Lock: factory installed, Operable from the front only;

#### inoperable from the rear. DEACTIVATE REAR DOORS/WINDOWS

- cc. Power Steering: factory installed
- dd. Protective Body Side Molding: factory installed
- ee. Quit sound group (special noise deadening insulation).
- ff. Radio: factory installed in dash AM/FM
- gg. Radio Suppression: radio frequency interference suppression measures and devices should be incorporated into the vehicle so that generated interference does not exceed the limits established in SAE standard J55, entitled "Measurement of Vehicle Radio Interference" (30 to 40 megacycles). hh. Rear Window Defrost.
- ii. Remote deck lid release, control on driver's side.

### jj. Roof Reinforcement for light bar installation.

- kk. Seats: bucket front and rear bench
- II. Speedometer: 160-mph or 260-km/h (certified) calibrated Speedometer. Allowable instrument error to be  $\pm$  one (1) mph at all Speeds between 10 and 100 mph.
- mm. Spotlight: factory installed, left side, not less than five (5) inches with aircraft or halogen bulb. nn. Suspension: Four-wheel independent performance suspension. Maximum handling package designed to limit body roll, allow flat cornering, limit dive on severe braking, limit squat on fast acceleration, and to provide optimum handling. Package should include, at a minimum, extra control front and rear shock absorbers, extra heavy duty frame or frame member reinforcement on unit frame, with front and rear stabilizer bars.
- oo. Tires: P225/60R18 BSW V-rated performance tires, pursuit radial. Tires must be certified by both the tire and auto manufacturer for police use to 120 mph sustained.
- pp. Wheels: heavy-duty, 18x7.5-inch steel wheels, full-size wheel covers for all wheels.
- qq. Windshield Wipers: intermittent type.
- rr. Upholstery: Heavy-duty, police duty, cloth front bucket seats and rear fixed vinyl bench seat. Color to coordinate with exterior color. Dark colors and black unacceptable due to heat build-up.
- B.2 Optional Equipment Purchaser may select the following:
  - BP. Ballistic Door Panels for driver or driver and passenger
  - CL. Disconnect dome lamp door courtesy light switches.
  - **DL. Daytime Running Lights**
  - MO. Delete Spotlight: Spotlight may be deleted for Credit
  - OO. Spotlight (additional, to be installed front passenger side).
  - VM. Vinyl Floor Mats, Front & Rear
  - WL. Full sized spare with tire to match others on vehicle
  - ZI. Street Appearance Package: **Front and Rear Cloth Seats**, Chrome grill, side moldings, full size wheel covers, change police engine markings. (Also deletes spotlight)

AWARD NO: SP-09-0028 PAGE 16

# ADDENDUM 11 TYPE MAB: Four (4) Door, Mid to Large Police Pursuit Sedan, **5.7L/V8 Hemi** (Dodge Charger no substitutes)

#### A. Size Classification

A.1 Vehicle shall have no more than 103 cubic feet of passenger interior space volume and a minimum of 15 cubic feet of trunk/cargo volume. Interior volumes are the ones shown as mid-size sedans in the latest <u>Fuel Economy Guide</u> published by the Environmental Protection Agency.

#### B. <u>Equipment</u>

- B.1 Standard Equipment Every–vehicle shall be equipped with the following:
  - a. Air Conditioning: Manual, factory installed and manufacturer standard tinted glass in all windows. Tint may be dealer installed but of same manufacturer as vehicle.
  - b. Alternator: high-output, minimum of 160 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control with tilt steering wheel (may be dealer installed, but of same manufacturer as vehicle).
  - e. Automatic Transmission: Five-Speed with overdrive.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Brakes: ABS type brake system and anti-slip rear axle.
  - h. Cooling System: Severe-duty including heavy duty extra capacity radiator, heavy duty temperature controlled fan, and factory installed coolant recovery system.
  - i. **Dome Lamp**: 12V LED/Incandescent.
  - j. Drive Axle: manufacturer to select axle ratio which will provide the best overall performance and the heaviest duty available.
  - k. Electric Controlled Door Locks: Operable from the front only; inoperable from the rear.
  - I. Engine: 5.7 liter V8 Hemi Engine with 355 hp @ 5000 rpm and 395 lb-ft of torque @ 4000 rpm. Suitable for police pursuit work and capable of accelerating from 0 to 60 mph in a maximum of 14.5 seconds with a minimum top Speed of 105 mph as shown in the latest Michigan Police Vehicle Test. Engine shall be 355 horsepower or larger equipped with dual exhaust (or single if larger enough for proper elimination of pressure) and factory installed engine oil cooler.
  - m. Engine Compartment Light
  - n. External Oil Coolers: engine oil, transmission fluid, power steering fluid.
  - o. Floor Mats: cloth, individual front and rear, color to coincide with interior.
  - p. Gauge Package: Warning lamps for low oil pressure, charging system, low fuel and coolant temperature
  - q. Glove Box Light.
  - r. Heater and Defroster
  - s. Horns: Dual
  - t. Inside hood latch control
  - u. License plate brackets: front and rear
  - v. Locks, Door: single key locking system for each car with three keys per vehicle. Separate key and key fob.
  - w. Mirrors, Rearview: with remote control both sides. None-glare, day-night inside.
  - x. Operator's Manual
  - v. Under hood lamp
  - z. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by the ordering entity.

AWARD NO: SP-09-0028 PAGE 17

#### Continue

ADDENDUM 11 TYPE MAB: Four (4) Door Mid to Large Police Pursuit Sedan, 5.7L/V8 Hemi (Dodge Charger no substitutes)

- aa. Police Package: including all features listed in manufacturer's printed specifications and literature part of police equipment package.
- bb. Power Window and Door Lock: factory installed, **Operable from the front only**; **inoperable from the rear. DEACTIVATE REAR DOORS/WINDOWS**
- cc. Power Steering: factory installed
- dd. Protective Body Side Molding: factory installed
- ee. Quit sound group (special noise deadening insulation).
- ff. Radio: factory installed in dash AM/FM
- gg. Radio Suppression: radio frequency interference suppression measures and devices should be incorporated into the vehicle so that generated interference does not exceed the limits established in SAE standard J55, entitled "Measurement of Vehicle Radio Interference" (30 to 40 megacycles).
- hh. Rear Window Defrost.
- ii. Remote deck lid release, control on driver's side.
- jj. Roof Reinforcement for light bar installation.
- kk. Seats: bucket front and rear bench
- II. Speedometer: 160-mph or 260-km/h (certified) calibrated Speedometer. Allowable instrument error to be  $\pm$  one (1) mph at all Speeds between 10 and 100 mph. mm. Spotlight: factory installed, left side, not less than five (5) inches with aircraft or halogen bulb
- nn. Suspension: Four-wheel independent performance suspension. Maximum handling package designed to limit body roll, allow flat cornering, limit dive on severe braking, limit squat on fast acceleration, and to provide optimum handling. Package should include, at a minimum, extra control front and rear shock absorbers, extra heavy duty frame or frame member reinforcement on unit frame, with front and rear stabilizer bars.
- oo. Tires: P225/60R18 BSW V-rated performance tires, pursuit radial. Tires must be certified by both the tire and auto manufacturer for police use to 120 mph sustained.
- pp. Wheels: heavy-duty, 18x7.5-inch steel wheels, **full-size wheel covers for all wheels**. qq. Windshield Wipers: intermittent type.
- rr. Upholstery: Heavy-duty, police duty, cloth front bucket seats and rear fixed vinyl bench seat. Color to coordinate with exterior color. Dark colors and black unacceptable due to heat build-up.
- B.2 Optional Equipment Purchaser may select the following:
  - BP. Ballistic Door Panels for driver or driver and passenger
  - CL. Disconnect dome lamp door courtesy light switches.
  - **DL. Daytime Running Lights**
  - MO. Delete Spotlight: Spotlight may be deleted for Credit
  - OO. Spotlight (additional, to be installed front passenger side).
  - VM. Vinyl Floor Mats, Front & Rear
  - WL. Full sized spare with tire to match others on vehicle
  - ZI. Street Appearance Package: **Front and Rear Cloth Seats**, Chrome grill, side moldings, full size wheel covers, change police engine markings. (Also deletes spotlight)

AWARD NO: SP-09-0028 PAGE 18

\*

# STATE OF ARKANSAS DEPARTMENT OF FINANCE AND ADMINISTRATION OFFICE OF STATE PROCUREMENT

#### STANDARD SPECIFICATIONS FOR TRUCKS, ONE (1) TON AND LESS

#### 1. SCOPE AND CLASSIFICATION:

- 1.1 Scope To set forth the minimum acceptable standards in obtaining trucks of (1) one ton or less capacity in conjunction with this specification and the states requirements.
- 1.2 Classification Vehicles covered herein shall be of the following types and options as specified in the contract award:

TYPE PAA - Compact Pickup Truck; see addendum 1, page 21

TYPE PAB - Compact Pickup Truck, Extended Cab; see addendum 2, page 22

TYPE PAD – Compact Pickup Truck, 4x4, Extended Cab, Four (4) Doors, Short Bed see addendum 2A, page 23

TYPE PBA - Full Size 1/2 Ton Pickup Truck, 6-Cylinder; see addendum 3, page 24

TYPE PBB - Full Size 1/2 Ton Pickup Truck, 6-Cylinder, Extended Cab, 4 doors see addendum 4, page 24

TYPE PBC - Full Size 1/2 Ton Pickup Truck, 6-Cylinder, **Crew or Quad Cab**, 4 doors; see addendum 5, page 26

TYPE PGA - Full Size 1/2 Ton Pickup Truck, 8-Cylinder; see addendum 6, page 27

TYPE PGB - Full Size 1/2 Ton Pickup Truck, 8-Cylinder, Extended Cab, Long Bed; see addendum 7, page 28

TYPE PGC - Full Size 1/2 Ton Pickup Truck, 8-Cylinder, **Crew or Quad Cab**, Long Bed; see addendum 8, page 29

TYPE PGD – Heavy-Duty 1/2 Ton Pickup Truck, 8-Cylinder, Long Bed; see addendum 9, page 30

TYPE PGE – Heavy-Duty 1/2 Ton Pickup Truck, 8-Cylinder, Extended Cab, Long Bed; see addendum 10, page 31

TYPE PGF - Heavy-Duty 1/2 Ton Pickup Truck, 8-Cylinder, **Crew or Quad Cab**, Long Bed; see addendum 11, page 32

TYPE PCA – Full Size 4x4, 1/2 Ton Pickup Truck, 6-Cylinder; see addendum 12, page 33 TYPE PCB – Full Size 4x4 1/2 Ton Pickup Truck, 6-Cylinder, Extended Cab, Long Bed;

see addendum 13, page 34

TYPE PCC – Full Size 4x4 1/2 Ton Pickup Truck, 6-Cylinder, **Crew or Quad Cab**, Long Bed; see addendum 14, page 35

TYPE PJA - Heavy-Duty 3/4 Ton Pickup Truck; see addendum 15, page 36

TYPE PJB – Heavy-Duty 3/4 Ton Pickup Truck, Extended Cab, Long Bed; see addendum 16, page 37

TYPE PJC - (not on contract, same as Type PJB) page 38

TYPE PJD – Heavy-Duty 3/4 Ton Pickup Truck, **Crew or Quad Cab**, Short Bed; see addendum 18, page 39

TYPE PEA - Heavy-Duty 4x4, 3/4 Ton Pickup Truck; see addendum 19, page 40

AWARD NO: SP-09-0028 PAGE 19

TYPE PEB – Heavy- Duty 4x4, 3/4 Ton Pickup Truck, Extended Cab, Long Bed; see addendum 20, page 41

TYPE PEC - (not on contract, same as Type PEB) page 42

TYPE PED – Heavy-Duty 4x4, 3/4 Ton Pickup Truck, Crew Cab, Long Bed; see addendum 22, page 43

TYPE PKA - Full Size One Ton Pickup Truck, Dually; see addendum 23, page 44

TYPE PKB - Full Size One Ton Pickup Truck, Dually, Extended Cab see addendum 24, page 45

TYPE PKC – Full Size One Ton Pickup Truck, Dually, **Crew or Quad Cab** see addendum 25, page 46

TYPE PQA - One-Ton Truck (Standard Chassis) Cab/Chassis Single Rear Wheels; see addendum 26, page 47

TYPE PQB - One-Ton Truck (Standard Chassis) Cab/Chassis, Single Rear Wheels, **Crew or Quad Cab**; see addendum 27, page 48

TYPE PRA - One-Ton Truck (Long Chassis) Cab/Chassis, Dual Rear Wheels see addendum 28, page 49

TYPE PRB - One-Ton Truck (Long Chassis) Cab/Chassis, Dual Rear Wheels, **Crew or Quad Cab**: see addendum 29, page 50

NOTE: Obtaining a cargo carrier other than those listed for a Type PQ or PR one-ton truck shall be the responsibility of the purchasing entity as an aftermarket option.

#### 2. APPLICABLE DOCUMENTS:

- 2.1 Reference to any standard(s), specification(s), amendment(s), and/or test method(s) shall be to the current issue(s) in effect on the date of the contract award.
- 2.2 Gasoline mileage shall conform to minimums shown in the latest edition of the Fuel Economy Guide published by the Environmental Protection Agency.

### 3. REQUIREMENTS:

3.1 All vehicles furnished to the State of Arkansas shall be new and delivered as specified within the contract award. Vehicles shall be furnished with all interior, exterior trim and appointments listed by the manufacturer in printed specifications and literature as standard equipment. Vehicles shall also be equipped with any and all safety equipment required by the State of Arkansas and/or applicable Federal Regulations. Any upgrades and/or additional equipment necessitated by selection of any listed option by the ordering entity shall be included in the price, and no additional charge shall be made by the vendor.

AWARD NO: SP-09-0028 PAGE 20

- 3.2 <u>Warranty</u> From date of delivery, each vehicle shall be accompanied by a warranty for a minimum of thirty six (36) months or thirty six thousand (36,000) miles, whichever comes first. Warranty shall certify that the vehicle is of good material and workmanship and that the replacement of any part or parts that fail under normal use within the designated period, free of negligence or accident, will be promptly repaired or replaced at NO cost to the agency, institution, or other public body that purchased the vehicle.
- 3.3 <u>Specific Requirements</u> See addenda 1 through 29 for specific requirements appropriate to each type of vehicle listed herein.

#### 4. <u>SAMPLING, INSPECTION, AND TEST PROCEDURES:</u>

4.1 Responsibility for inspection - Unless otherwise specified, the successful contractor will be responsible for performing all inspections required herein. The Office of State Procurement reserves the right to make any and all inspections deemed necessary to insure compliance with this specification.

#### 5. PREPARATION FOR DELIVERY:

Each vehicle shall be completely serviced, cleaned and thoroughly inspected by the successful contractor just prior to delivery to the purchasing entity. No dealer advertisement shall be on any vehicle purchased by the State of Arkansas.

#### PREDELIVERY REQUIREMENTS:

- a. Complete lubrication.
- b. Fill crankcase with oil.
- c. Adjustment of engine to proper operating conditions.
- d. Inflate tires to proper pressure.
- e. Careful check to assure perfect operation of all mechanical features.
- f. Front end alignment and wheels balanced.
- g. Cleaning of vehicle, if necessary, and removal of all unnecessary tags, stickers, papers, etc. Window price sticker shall not be removed
- h. No dealer's insignia shall be affixed to automobile.
- i. A minimum five gallons of fuel in each vehicle.
- j. Delivery shall be during normal working hours, 8 A.M. 4 P.M. Monday Friday.
- k. License plate holders installed, front and rear.

AWARD NO: SP-09-0028 PAGE 21

### **SPECIFICATION FOR TRUCKS: ONE (1) TON AND LESS**

<u>Note</u>: The engines listed in Standard Specification for pickup trucks must work with any option (NO ADDITIONAL COST) listed .

ADDENDUM 1: TYPE PAA: Compact Pickup Truck

#### A. Equipment:

- A.1 Standard Equipment Each long bed pickup truck shall be equipped as follows:
  - a. Air conditioning: factory installed, and manufacturer standard tinted glass in all windows.
  - b. Alternator: type recommended by manufacturer for truck as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: Maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy duty step type rear.
  - f. Engine: gasoline engine of manufacturer's standard size for truck as equipped.
  - g. Horsepower/Torque: minimum of 148 hp rating and 180 lb torque
  - h. License plate brackets: front and rear.
  - i. Long wide pickup box.
  - j. Mirrors: two (2) outside, low mount, right and left.
  - k. Operator's manual.
  - I. Paint: One (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - m. Power Brakes: Factory installed.
  - n. Power Steering.
  - o. Radio: factory installed in dash AM/FM.
  - p. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - q. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - r. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
- A.2 Optional Equipment Purchaser may select from the following:

## AO. Four wheel drive (4x4) with standard equipment and buyers' choice of options listed.

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short Wide Pickup Box.
- TO. Without air conditioning.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 22

\*

#### ADDENDUM 2: TYPE PAB: Compact Pickup Truck, Extended Cab

#### A. Equipment:

#### A.1 Standard Equipment - Each short bed pickup truck shall be equipped as follows:

- a. Air conditioning: factory installed, and manufacturer standard tinted glass in all windows.
- b. Alternator: type recommended by manufacturer for truck as equipped.
- c. Antifreeze: serviced to -29°C (-20°F) or lower.
- d. Battery: Maintenance free, type recommended by manufacturer for vehicle as equipped.
- e. Bumpers: standard front, heavy-duty step type rear.
- f. Engine: gasoline engine of manufacturer's standard size for truck as equipped.
- g. Horsepower/Torque: minimum of 148 hp rating and 180 lb torque
- h. License plate brackets: front and rear.
- i. Short wide pickup box.
- j. Mirrors: two (2) outside, low mount, right and left.
- k. Operator's manual.
- I. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
- m. Power brakes: Factory installed.
- n. Power steering.
- o. Radio: factory installed in dash AM/FM.
- p. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
- q. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
- r. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
- s. Extended cab

### A.2 Optional Equipment - Purchaser may select from the following:

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control (may be dealer installed but shall be from same manufacturer as vehicle) and tilt steering wheel.
- QH. Long Wide Pickup Box.
- TO. Without air conditioning.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 23

#### ADDENDUM 2A: TYPE PAD: Compact Pickup Truck, 4 x 4, Extended Cab, Four (4) Doors, Short Bed

#### A. Equipment:

- A.1 Standard Equipment Each short bed pickup truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy duty, minimum of 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling system: heavy duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: gasoline engine of the type recommended by manufacturer for vehicle as equipped.
  - h. Horsepower/Torque: minimum of 200 hp rating and 230 lb torque
  - i. Gauge: oil pressure.
  - j. Hubs: automatic locking.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Short wide box.
  - n. Mirrors: two (2) outside, low mount, right and left.
  - o. Operator's manual.
  - p. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - q. Power brakes: factory installed.
  - r. Power steering: factory installed.
  - s. Radio: factory installed in dash AM/FM.
  - t. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - u. Tires: five (5) radial tubeless, type recommended by manufacturer for vehicle as equipped.
  - v. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - w. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.

#### A.2 Optional Equipment - Purchaser may select from the following:

CB. Gasoline engine: 8-cylinder, a minimum of 280 cid.

- KO. Skid plate.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QH. Long Wide Pickup Box
- TO. Without air conditioning.
- UO. Transmission Oil coolers.
- XO. Hitch, Class III, frames attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 24

ADDENDUM 3: TYPE PBA: Full Size One-Half (1/2) Ton Pickup Truck, 6-Cylinder (Larger engine size not acceptable)

#### A. Equipment:

- A.1 Standard Equipment Each long bed pickup truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy duty, minimum 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy duty step type rear.
  - f. Cooling system: heavy duty, including heavy duty radiator, heavy duty fan, and factory installed coolant recovery system.
  - g. Engine: 6-cylinder gasoline engine of the type recommended by manufacturer for vehicle as equipped. Larger engine size not acceptable
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup box.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering.
  - p. Radio: factory installed in dash AM/FM.
  - q. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - r. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - s. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
- A.2 Optional Equipment Purchaser may select from the following:

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup box.
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 25

\*

ADDENDUM 4: TYPE PBB: Full Size One-Half (1/2) Ton Pickup Truck, Short Bed, 6-Cylinder, Extended Cab, Rear Seat, Four (4) Doors (Larger engine size not acceptable)

#### A. <u>Equipment:</u>

#### A.1 Standard Equipment - Each short bed pickup truck shall be equipped as follows:

- a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
- b. Alternator: heavy duty, minimum 40 amperes.
- c. Antifreeze: serviced to -29°C (-20°F) or lower.
- d. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
- e. Bumpers: standard front, heavy-duty step type rear.
- f. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
- g. Engine: 6-cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped. Larger engine size not acceptable
- h. Inside hood latch control.
- i. License plate brackets: front and rear.
- j. Short wide pickup box.
- k. Mirrors: two (2) outside, low mount, right and left.
- I. Operator's manual.
- m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
- n. Power brakes: factory installed.
- o. Power steering.
- p. Radio: factory installed in dash AM/FM.
- q. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
- r. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
- s. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
- t. Extended Cab w/rear seat, four doors.

#### A.2 Optional Equipment - Purchaser may select from the following:

- DS. Without Rear Seat
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle)
- QH. Long Wide Pickup Box
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 26

ADDENDUM 5: TYPE PBC: Full Size One-Half (1/2) Ton Pickup Truck, Short Bed, **Crew/Quad Cab**, 6-Cylinder, Rear Seat, Four (4) Doors (Larger engine size not acceptable)

### A. Equipment:

- A.1 Standard Equipment Each short bed pickup truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy duty, minimum 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy duty step type rear.
  - f. Cooling system: heavy duty, including heavy duty radiator, heavy duty fan, and factory installed coolant recovery system.
  - g. Engine: 6-cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped. Larger engine size not acceptable
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Short wide pickup box.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering.
  - p. Radio: factory installed in dash AM/FM.
  - q. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - r. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - s. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
  - t. Crew/Quad Cab with rear seat, 4 doors.
- A.2 Optional Equipment Purchaser may select from the following:

- DS. Without Rear Seat
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QH. Long wide pickup box.
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 27

#### ADDENDUM 6: TYPE PGA: Full Size One-Half (1/2) Ton Pickup Truck, 8-Cylinder

#### A. Equipment:

- A.1 Standard Equipment Each long bed pickup truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy duty, minimum 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommend by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline fueled engine, a minimum of 280 cid.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - r. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - s. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
- A.2 Optional Equipment Purchaser may select from the following:

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup box.
- TO. Without air conditioning.
- UO. Transmission oil cooler, Mfr. or dealer installed.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 28

ADDENDUM 7: TYPE PGB: Full Size One-Half (1/2) Ton Pickup Truck, 8-Cylinder, Long Bed, Extended Cab, Rear Seat, Four (4) Doors

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy duty, minimum 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommend by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline engine, a minimum of 280 cid.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - r. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - s. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
  - t. Extended cab w/rear seat, four (4) doors.
- A.2 Optional Equipment Purchaser may select from the following:

- DS. Without Rear Seat
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- TO. Without air conditioning.
- UO. Transmission Oil coolers.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 29

ADDENDUM 8: TYPE PGC: Full Size One-Half (1/2) Ton Pickup Truck, 8-Cylinder, Long Bed, **Crew/Quad Cab**, Rear Seat, Four (4) Doors

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommend by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline fueled engine, a minimum of 280 cid.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - r. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - s. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
  - t. Crew/Quad Cab, Rear Seat, 4 Doors.
- A.2 Optional Equipment Purchaser may select from the following:

- DS. Without Rear Seat
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- TO. Without air conditioning.
- UO. Transmission Oil coolers.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 30

### ADDENDUM 9: TYPE PGD: One Half (1/2) Ton Heavy Duty Pickup Truck, 8-cylinder, Long Bed

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy duty, type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline fueled engine, a minimum of 280 CID.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - r. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - s. Transmission: **heavy-duty**, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - t. Upholstery: manufacturer's standard materials and color to coincide with exterior color.
  - u. Payload package for heavy-duty use.
- A.2 Optional Equipment Purchaser may select from the following:

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- TO. Without air conditioning.
- UO. Transmission Oil coolers.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 31

ADDENDUM 10: TYPE PGE: One Half (1/2) Ton Heavy-Duty Pickup Truck, 8-cylinder, Extended Cab, Long Bed, Rear Seat, Four (4) Doors

#### A. <u>Equipment:</u>

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline fueled engine, a minimum of 280 CID.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's Manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - r. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - s. Transmission: **heavy-duty**, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - t. Upholstery: manufacturer's standard materials and color to coincide with exterior color.
  - u. Extended cab with rear seat, four (4) doors.
  - v. Payload package for heavy-duty use.
- A.2 Optional Equipment Purchaser may select from the following:

#### **DL. Daytime Running Lights**

- DS. Without Rear Seat.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- TO. Without air conditioning.
- UO. Transmission Oil coolers.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped.

Must be dealer or manufacturer installed. Insert bar and ball not included.

ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 32

ADDENDUM 11: TYPE PGF: One Half (1/2) Ton Heavy-Duty Pickup Truck, 8-cylinder **Crew/Quad Cab**, Long Bed, Rear Seat, Four (4) Doors

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline fueled engine, a minimum of 280 CID.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's Manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - r. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - s. Transmission: **heavy-duty**, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - t. Upholstery: manufacturer's standard materials and color to coincide with exterior color.
  - u. Crew/Quad Cab with rear seat, four (4) doors
  - v. Payload package for heavy use.
- A.2 Optional Equipment Purchaser may select from the following:

- DS. Without Rear Seat.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- TO. Without air conditioning.
- UO. Transmission Oil coolers.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 33

### ADDENDUM 12: TYPE PCA: Full Size 4x4 One-Half (1/2) Ton Pickup Truck, 6-cylinder

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum of 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 6-cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - h. Gauge: oil pressure.
  - i. Hubs: automatic locking.
  - j. Inside hood latch control.
  - k. License plate brackets: front and rear.
  - I. Long wide pickup bed.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - g. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - t. Tires: five (5) radial tubeless, type recommended by manufacturer or vehicle as equipped.
  - u. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
- A.2 Optional Equipment Purchaser may select from the following:
  - CB. Gasoline Engine: 8-cylinder, a minimum of 280 cid.
  - **DL. Daytime Running Lights**
  - KO. Skid plate.
  - LS. Differential: limited slip, ratio as recommended by manufacturer.
  - PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
  - QI. Short wide pickup bed.
  - TO. Without air conditioning.
  - UO. Transmission Oil Coolers.
  - XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped Must be dealer or manufacturer installed. Insert bar and ball not included.
  - ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 34

ADDENDUM 13: TYPE PCB: Full Size 4x4 One-Half (1/2) Ton Pickup Truck, 6-cylinder Extended Cab, Long Bed, Rear Seat, Four (4) Doors

#### A. <u>Equipment:</u>

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum of 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 6-cylinder gasoline engine of the type recommended by manufacturer for vehicle as equipped.
  - h. Gauge: oil pressure.
  - i. Hubs: automatic locking.
  - j. Inside hood latch control.
  - k. License plate brackets: front and rear.
  - I. Long wide pickup bed.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - g. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - t. Tires: five (5) radial tubeless, type recommended by manufacturer or vehicle as equipped.
  - u. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
  - w. Extended cab w/rear seat, four (4) doors.
- A.2 Optional Equipment Purchaser may select from the following:
  - CB. Gasoline engine: 8-cylinder, a minimum of 280 cid.
  - **DL. Daytime Running Lights**
  - DS. Without Rear Seat.
  - KO. Skid plate.
  - LS. Differential: limited slip, ratio as recommended by manufacturer.
  - PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
  - QI. Short wide pickup bed.
  - TO. Without air conditioning.
  - UO. Transmission Oil coolers.
  - XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
  - ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 35

ADDENDUM 14: TYPE PCC: Full Size 4x4 One-Half (1/2) Ton Pickup Truck, 6-cylinder **Crew/Quad Cab** Long Bed, Rear Seat, Four (4) Doors

#### A. <u>Equipment:</u>

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum of 40 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 6-cylinder gasoline engine of the type recommended by manufacturer for vehicle as equipped.
  - h. Gauge: oil pressure.
  - i. Hubs: automatic locking.
  - j. Inside hood latch control.
  - k. License plate brackets: front and rear.
  - I. Long wide pickup bed.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - g. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - t. Tires: five (5) radial tubeless, type recommended by manufacturer or vehicle as equipped.
  - u. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
  - w. Crew/Quad Cab w/rear seat, four (4) Doors
- A.2 Optional Equipment Purchaser may select from the following:
  - CB. Gasoline Engine: 8-cylinder, a minimum of 280 cid.

- KO. Skid plate.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- TO. Without air conditioning.
- UO. Transmission Oil Cooler.
- XO. Hitch, Class III, frame attached, type recommended by manufacturer for vehicle as equipped. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 36

#### ADDENDUM 15: TYPE PJA: Three-Quarter (3/4) Ton Heavy Duty Pickup Truck, 8-cylinder

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. GVWR: shall be 8600 or better.
  - g. Engine: 8-cylinder gasoline engine, a minimum of 325 CID.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's Manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - g. Suspension: type recommended by manufacturer for vehicle as equipped.
  - r. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - s. Trailering Package: to include an engine oil and transmission cooler.
  - t. Transmission: heavy duty, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - u. Upholstery: manufacturer's standard materials and color to coincide with exterior color.
- A.2 Optional Equipment Purchaser may select from the following:

#### **BD. 20 % Bio Diesel under OEM Warranty**

- BO. Differential with gear ratio designed for extra towing capability.
- **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 37

ADDENDUM 16: TYPE PJB - Three-Quarter (3/4) Ton Heavy Duty Pickup Truck, 8-cylinder Extended Cab Long Bed, Rear Seat, Four (4) Doors

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. GVWR: shall be 8600 or better.
  - g. Engine: 8-cylinder gasoline engine, a minimum of 325 CID.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Suspension: type recommended by manufacturer for vehicle as equipped.
  - r. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - s. Trailering package: to include an engine oil and transmission cooler.
  - t. Transmission: heavy duty, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - u. Upholstery: manufacturer's standard materials and color to coincide with exterior color.
  - v. Extended cab with rear seat, four (4) doors.
- A.2 Optional Equipment Purchaser may select from the following:
  - BO. Differential with gear ratio designed for extra towing capability.
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.

- DS. Without Rear Seat
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 38

ADDENDUM 17: TYPE PJC - Three-Quarter (3/4) Ton Heavy Duty Pickup Truck, 8-cylinder Extended Cab, Long Bed, Rear Seat, Four (4) Doors (NOT ON CONTRACT, SAME AS TYPE PJB)

## A. <u>Equipment</u>:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. GVWR: shall be 8600 or better.
  - g. Engine: 8-cylinder gasoline engine, a minimum of 325 CID.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's Manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Suspension: type recommended by manufacturer for vehicle as equipped.
  - r. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - s. Trailering Package: to include an external engine oil and transmission cooler.
  - t. Transmission: heavy-duty, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - u. Upholstery: manufacturer's standard materials and color to coincide with exterior color.
  - v. Extended Cab with rear seat, four (4) doors.
- A.2 Optional Equipment Purchaser may select from the following:
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - BO. Differential with gear ratio designed for extra towing capability.
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.

- DS. Without Rear Seat.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 39

ADDENDUM 18: TYPE PJD - Three-Quarter (3/4) Ton Heavy Duty Pickup Truck 8-cylinder Crew Cab, Long Bed, Full Size Rear Bench Seat, Four (4) Full Doors

### A. <u>Equipment</u>:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, type recommended by manufacturer for vehicle as equipped.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. GVWR: shall be 8600 or better.
  - g. Engine: 8-cylinder gasoline engine, a minimum of 325 CID.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed.
  - p. Radio: factory installed in dash AM/FM.
  - q. Suspension: type recommended by manufacturer for vehicle as equipped.
  - r. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - s. Trailering Package: to include an engine oil and transmission cooler.
  - t. Transmission: heavy duty, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - u. Upholstery: manufacturer's standard materials and color to coincide with exterior color.
  - v. Crew Cab w/full size rear bench seat, four (4) full doors.
- A.2 Optional Equipment Purchaser may select from the following:
  - BO. Differential with gear ratio designed for extra towing capability.
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.

- GO. Carrier: spare wheel, side mount.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short pickup bed.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 40

## ADDENDUM 19: TYPE PEA - 4x4, Three-Quarter (3/4) Ton Heavy Duty Pickup Truck, 8-cylinder

## A. <u>Equipment:</u>

- A.1 Standard Equipment Each long wide pickup bed truck obtained by this specification shall have a minimum GVW of 8600 lbs and be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy duty, minimum 60 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline engine, a minimum of 325 CID.
  - h. Gauge: oil pressure.
  - i. Hubs: automatic locking.
  - j. Inside hood latch control.
  - k. License plate brackets: front and rear.
  - I. Long wide pickup bed.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - q. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - t. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - u. Transmission: automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
- A.2 Optional Equipment: Purchaser may select from the following:

### **BD. 20 % Bio Diesel under OEM Warranty**

**CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.

- KO. Skid plate.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short Wide Pickup Bed
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 41

ADDENDUM 20: TYPE PEB - 4x4 Three-Quarter (3/4) Ton Heavy Duty Pickup Truck, 8-cylinder Extended Cab, Long Bed, Rear Seat, Four (4) Doors

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck obtained by this specification shall have a minimum GVW of 8600 lbs and be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum 60 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline fueled engine, a minimum of 325 CID.
  - h. Gauge: oil pressure.
  - i. Hubs: automatic locking.
  - j. Inside hood latch control.
  - k. License plate brackets: front and rear.
  - I. Long wide pickup bed.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - g. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - t. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - u. Transmission: heavy-duty, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
  - w. Extended Cab w/rear seat, four (4) doors.
- A.2 Optional Equipment: Purchaser may select from the following:
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.

- DS. Without Rear Seat.
- KO. Skid plate.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short Wide Pickup Bed
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 42

ADDENDUM 21: TYPE PEC - 4x4 Three-Quarter (3/4) Ton Heavy Duty Pickup Truck, 8-cylinder, Long Bed Extended Cab, Rear Seat, Four (4) Doors (NOT ON CONTRACT, SAME AS TYPE PEB)

#### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck obtained by this specification shall have a minimum GVW of 8600 lbs and be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum 60 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline fueled engine, a minimum of 325 CID.
  - h. Gauge: oil pressure.
  - i. Hubs: automatic locking.
  - j. Inside hood latch control.
  - k. License plate brackets: front and rear.
  - I. Long wide pickup bed.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - q. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - t. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - u. Transmission: heavy-duty, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
  - w. Extended Cab w/rear seat, four (4) doors.
- A.2 Optional Equipment: Purchaser may select from the following:

## **BD. 20 % Bio Diesel under OEM Warranty**

**CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.

- DS. Without Rear Seat.
- KO. Skid plate.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short wide pickup bed.
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or Manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 43

ADDENDUM 22: TYPE PED - 4x4, Three-Quarter (3/4) Ton Heavy Duty Pickup Truck, 8-cylinder Crew Cab, Rear Bench Seat, Four (4) Full Doors

#### A. <u>Equipment:</u>

- A.1 Standard Equipment Each long wide pickup bed truck obtained by this specification shall have a minimum GVW of 8600 lbs and be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum 60 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: 8-cylinder gasoline engine, a minimum of 325 CID.
  - h. Gauge: oil pressure.
  - i. Hubs: automatic locking.
  - j. Inside hood latch control.
  - k. License plate brackets: front and rear.
  - I. Long wide pickup bed.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - g. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - t. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - u. Transmission: heavy-duty, automatic, with a minimum of three (3) forward Speeds and one (1) reverse.
  - v. Upholstery: manufacturer's standard materials and colors to coincide with exterior color.
  - w. Crew Cab w/rear bench seat, four (4) full doors.
- A.2 Optional Equipment: Purchaser may select from the following:

#### **BD. 20 % Bio Diesel under OEM Warranty**

**CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.

- KO. Skid plate.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- QI. Short pickup bed.
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZO. Transmission: manual, with a minimum of three (3) forward Speeds and one (1) reverse.

AWARD NO: SP-09-0028 PAGE 44

## ADDENDUM 23: TYPE PKA - Full Size One (1) Ton Pickup Truck, Dually

### A. <u>Equipment:</u>

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air Conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum 95 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: minimum of a 325 CID with rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's Manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed.
  - p. Radio: factory installed AM/FM.
  - q. Tires and Rims: seven (7) steel wheels with all season, steel belted radial tubeless black-wall as recommended by manufacturer for size and load range of vehicle as equipped.
  - r. Trailering Package: to include oil cooler and transmission (auto transmission only) cooler.
  - s. Transmission: heavy duty five (5) Speed manual with overdrive.
  - t. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
- A.2 Optional Equipment Purchaser may select from the following:
  - AO. Four wheel drive (4x4) (with standard equipment and buyers' choice of options listed).
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities
  - CD. Gasoline Engine: Min. 8-cylinder, a minimum of 414 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZP. Transmission: Four (4) Speed Automatic.

AWARD NO: SP-09-0028 PAGE 45

ADDENDUM 24: TYPE PKB - Full Size One (1) Ton Pickup Truck, Dually, Extended Cab

### A. <u>Equipment:</u>

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum 95 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling system: heavy-duty, including heavy-duty radiator, heavy duty fan, and factory installed coolant recovery system.
  - g. Engine: minimum of a 325 CID with rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering: factory installed.
  - p. Radio: factory installed AM/FM.
  - q. Tires and Rims: seven (7) steel wheels with all season, steel belted radial tubeless black-walls as recommended by manufacturer for size and load range of vehicle as equipped.
  - r. Trailering Package: to include oil cooler and transmission (auto transmission only) cooler.
  - s. Transmission: heavy-duty five (5) Speed manual with overdrive.
  - t. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
  - u. Extended Cab
- A.2 Optional Equipment Purchaser may select from the following:
  - AO. Four wheel drive (4x4) (with standard equipment and buyers choice of options listed).
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities
  - CD. Gasoline Engine: Min. 8 cylinder, a minimum of 414 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZP. Transmission: Four (4) Speed Automatic.

AWARD NO: SP-09-0028 PAGE 46

## ADDENDUM 25 TYPE PKC - Full Size One (1) Ton Pickup Truck, Dually, Crew/Quad Cab

### A. Equipment:

- A.1 Standard Equipment Each long wide pickup bed truck shall be equipped as follows:
  - a. Air conditioning: factory installed and manufacturer standard tinted glass in all windows.
  - b. Alternator: heavy-duty, minimum 95 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front, heavy-duty step type rear.
  - f. Cooling system: heavy-duty, including heavy-duty radiator, heavy duty fan, and factory installed coolant recovery system.
  - g. Engine: minimum of a 325 CID with rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.
  - h. Inside hood latch control.
  - i. License plate brackets: front and rear.
  - j. Long wide pickup bed.
  - k. Mirrors: two (2) outside, low mount, right and left.
  - I. Operator's manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering: factory installed.
  - p. Radio: factory installed AM/FM.
  - q. Tires and Rims: seven (7) steel wheels with all season, steel belted radial tubeless black-walls as recommended by manufacturer for size and load range of vehicle as equipped.
  - r. Trailering Package: to include oil cooler and transmission (auto transmission only) cooler.
  - s. Transmission: heavy-duty five (5) Speed manual with overdrive.
  - t. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
  - u. Crew/Quad Cab
- A.2 Optional Equipment Purchaser may select from the following:
  - AO. Four wheel drive (4x4) (with standard equipment and buyers' choice of options listed).
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities
  - CD. Gasoline Engine: Min. 8 cylinder, a minimum of 414 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- TO. Without air conditioning.
- XO. Hitch, Class III, frame attached, 7500 lb or better towing capacity. Must be dealer or manufacturer installed. Insert bar and ball not included.
- ZP. Transmission: Four (4) Speed Automatic.

AWARD NO: SP-09-0028 PAGE 47

ADDENDUM 26: TYPE PQA - One (1) Ton Truck Standard Chassis Single Rear Wheel Type Chassis/Cab (w/out bed), minimum of 133 inches

#### A. <u>Equipment:</u>

- A.1 Standard Equipment Chassis/cab shall be a minimum of one hundred thirty three (133) inches long and shall be equipped as follows:
  - a. Air Conditioning: factory installed.
  - b. Alternator: heavy-duty, a minimum of 95 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: minimum of a 325 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.
  - h. Gauges: a minimum of engine temperature, fuel, oil pressure, Speedometer, and voltmeter.
  - i. Inside hood latch control.
  - j. License plate brackets: front and rear.
  - k. Mirrors: two (2) outside, camper type extended view.
  - I. Operator's Manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed.
  - p. Radio: factory installed AM/FM.
  - q. Tires and Rims: five (5) steel wheels (2 front, 2 rear plus matching spare) with all season steel belted radial tubeless black-walls as recommended by manufacturer for size and load range of vehicle as equipped.
  - r. Transmission: heavy duty five (5) Speed manual with overdrive.
  - s. Upholstery: manufacturers standard materials and colors to coincide with exterior color chosen.
- A.2 Optional Equipment Purchaser's may select from the following:
  - AO. Four wheel drive (4x4) (with standard equipment and buyers' choice of options listed).
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities
  - CD. Gasoline Engine: 8-cylinder, minimum of 414 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.

- GG. Dual Rear Wheels.
- LS. Differential: limited slip, ratio as recommended by manufacturer for maximum use of cargo carrier selected.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- TO. Without air conditioning.
- ZP. Transmission: Four (4) Speed Automatic.

AWARD NO: SP-09-0028 PAGE 48

ADDENDUM 27: TYPE PQB - One (1) Ton Truck Standard Chassis Single Rear Wheel Type, Crew/Quad Cab, Chassis/Cab (w/out bed), minimum of **176 inches** 

#### A. Equipment:

- A.1 Standard Equipment Chassis/cab shall be a minimum of one hundred **seventy-six (176) inches** long and shall be equipped as follows:
  - a. Air conditioning: factory installed.
  - b. Alternator: heavy-duty, a minimum of 95 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front.
  - f. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: minimum of a 325 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.
  - h. Gauges: a minimum of engine temperature, fuel, oil pressure, speedometer, and voltmeter.
  - i. Inside hood latch control.
  - j. License plate brackets: front and rear.
  - k. Mirrors: two (2) outside, camper type extended view.
  - I. Operator's manual.
  - m. Paint: One (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power brakes: factory installed.
  - o. Power steering: factory installed.
  - p. Radio: factory installed AM/FM.
  - q. Tires and rims: five (5) steel wheels (2 front, 2 rear plus spare) with all season steel belted radial tubeless black-walls as recommended by manufacturer for size and load range of vehicle as equipped.
  - r. Transmission: heavy duty five (5) Speed manual with overdrive.
  - s. Upholstery: manufacturers' standard materials and colors to coincide with exterior color chosen.
  - t. Crew Cab, with rear seat, four (4) full doors.
- A.2 Optional Equipment Purchaser may select from the following:
  - AO. Four wheel drive (4x4) with standard equipment and buyers' choice of options listed.

#### **BD. 20 % Bio Diesel under OEM Warranty**

- **CA. Diesel Engine**: minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities
- CD. Gasoline Engine: 8-cylinder, minimum of 414 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.

- GG. Dual Rear Wheels.
- LS. Differential: limited slip, ratio as recommended by manufacturer for maximum use of cargo carrier selected.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- TO. Without air conditioning.
- ZP. Transmission: Four (4) Speed Automatic.

AWARD NO: SP-09-0028 PAGE 49

ADDENDUM 28: TYPE PRA - One (1) Ton Truck Long Chassis, Dual Rear Wheels Chassis/Cab (w/out bed), minimum 159 inches and minimum of 11,000 lb GVWR

#### A. Equipment:

- A.1 Standard Equipment Chassis/cab shall be a minimum of one hundred fifty nine (159) inches long with a minimum eleven thousand 11,000) pounds GVWR and shall be equipped as follows:
  - a. Air Conditioning: factory installed.
  - b. Alternator: heavy-duty, a minimum of 95 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: minimum of a 325 CID with an axle ratio suggested by manufacturer to maximize vehicles highway performance and towing capabilities.
  - h. Gauges: a minimum of engine temperature, fuel, oil pressure, speedometer, and voltmeter.
  - i. Inside hood latch control.
  - j. License plate brackets: front and rear.
  - k. Mirrors: two (2) outside, camper type extended view.
  - I. Operator's Manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed
  - p. Radio: factory installed AM/FM.
  - q. Tires and Rims: seven (7) steel wheels (2 front, 4 rear plus spare) with all season steel belted radial tubeless black-walls as recommended by manufacturer for size and load range of vehicle as equipped.
  - r. Transmission: heavy duty five (5) Speed manual with overdrive.
  - s. Upholstery: manufacturer standard materials and colors to coincide with exterior color chosen.
- A.2 Optional Equipment Purchaser may select from the following:
  - AO. Four wheel drive (4x4) (with standard equipment and buyers' choice of options listed).
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **CA. Diesel Engine**: a minimum of 190 HP with a rear axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities
  - CD. Gasoline Engine: Min. 8-cylinder, a minimum of 414 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.

- LS. Differential: limited slip, ratio as recommended by manufacturer for maximum use of cargo carrier selected.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- TO. Without air conditioning.
- ZP. Transmission: Four (4) Speed Automatic.

AWARD NO: SP-09-0028 PAGE 50

ADDENDUM 29: TYPE PRB - One (1) Ton Truck Long Chassis, Dual Rear Wheels Crew Cab Chassis/Cab (w/out bed), minimum 176 inches and minimum 11,000 lb GVWR

#### A. <u>Equipment:</u>

- A.1 Standard Equipment Chassis/cab shall be a minimum of one hundred seventy-six (176) inches long with a minimum eleven thousand (11,000) pounds GVWR and shall be equipped as follows:
  - a. Air Conditioning: factory installed.
  - b. Alternator: heavy-duty, a minimum of 95 amperes.
  - c. Antifreeze: serviced to -29°C (-20°F) or lower.
  - d. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - e. Bumpers: standard front.
  - f. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - g. Engine: minimum of a 325 CID with an axle ratio suggested by manufacturer to maximize vehicles highway performance and towing capabilities.
  - h. Gauges: a minimum of engine temperature, fuel, oil pressure, speedometer, and voltmeter.
  - i. Inside hood latch control.
  - j. License plate brackets: front and rear.
  - k. Mirrors: two (2) outside, camper type extended view.
  - I. Operator's Manual.
  - m. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - n. Power Brakes: factory installed.
  - o. Power Steering: factory installed
  - p. Radio: factory installed AM/FM.
  - q. Tires and Rims: seven (7) steel wheels (2 front, 4 rear, plus spare) with all season steel belted radial tubeless black-walls as recommended by manufacturer for size and load range of vehicle as equipped.
  - r. Transmission: heavy-duty five (5) Speed manual with overdrive.
  - s. Upholstery: manufacturer's standard materials and colors to coincide with exterior color chosen.
  - t. Crew Cab w/rear seat, four (4) full doors.
- A.2 Optional Equipment Purchaser may select from the following:
  - AO. Four wheel drive (4x4) with standard equipment and buyers' choice of options listed.

#### **BD. 20 % Bio Diesel under OEM Warranty**

- **CA. Diesel Engine**: min of a 190 hp with a rear wheel axle ratio as recommended by manufacturer to maximize the vehicles highway performance and towing capabilities.
- CD. Gasoline Engine: Min. 8 cylinder, a minimum of 414 CID with a rear axle ratio suggested by manufacturer to maximize the vehicles highway performance and towing capabilities.

- LS. Differential: limited slip, ratio as recommended by manufacturer for maximum use of cargo carrier selected.
- PO. Automatic Speed Control with tilt steering wheel (may be dealer installed but shall be from same manufacturer as vehicle).
- TO. Without air conditioning.
- ZP. Transmission: four (4) Speed Automatic.

AWARD NO: SP-09-0028 PAGE 51

## STATE OF ARKANSAS DEPARTMENT OF FINANCE AND ADMINISTRATION OFFICE OF STATE PROCUREMENT

## STANDARD SPECIFICATIONS FOR VANS, CARRYALLS AND UTILITY VEHICLES

#### 1. SCOPE AND CLASSIFICATION:

- Scope To set forth the minimum purchasing standards in obtaining vans and utility vehicles 1.1 in conjunction with this specification and the states requirements.
- 1.2 Classification - Vehicles covered herein shall be of the following types and options as specified in the contract award:

TYPE VAA – Full Size 1/2 Ton Utility Van; see addendum 1, page 53

TYPE VAB - Full Size 3/4 Ton Utility Van; see addendum 2, page 54

TYPE VAC - Full Size 1 Ton Utility Van; see addendum 3, page 55

TYPE VBA - Full Size 1/2 Ton 8-Passenger Van; see addendum 4, page 56

TYPE VGA - 3/4 Ton 8-Passenger Van; see addendum 5, page 57

TYPE VCA - 1 Ton 12-Passenger Van; see addendum 6, page 58

TYPE VDA - 1 Ton 15-Passenger Van; see addendum 7, page 59

TYPE VEA - Compact Utility Van; see addendum 8, page 60

TYPE VFA - Compact 7-Passenger Van; see addendum 9, page 61

TYPE PHA - Compact 2 WD Utility Vehicle; see addendum 10, page 62

TYPE PHB - Compact 4 WD Utility Vehicle; see addendum 11, page 63

TYPE PHC - Compact AWD Utility Vehicle; see addendum 12, page 64

TYPE PIA – Midsize 2 WD Utility Vehicle; see addendum 13, page 65

TYPE PIB - Midsize 4 WD Utility Vehicle; see addendum 14, page 66

TYPE PSA – Full Size 2 WD Utility Vehicle; see addendum 15, page 67

TYPE PSB - Full Size 4 WD Utility Vehicle; see addendum 16, page 68 TYPE PMA - 8-Passenger Carryall; see addendum 17, page 69

## 2. APPLICABLE DOCUMENTS:

- 2.1 Reference to any standard(s), specification(s), amendment(s), and/or test method(s) shall be to the current issue(s) in effect on the date of the contract award.
- 2.2 Gasoline mileage shall conform to minimums shown in the latest edition of the Fuel Economy <u>Guide</u> published by the Environmental Protection Agency.

AWARD NO: SP-09-0028 PAGE 52 

## 3. REQUIREMENTS:

- 3.1 All vehicles furnished to the State of Arkansas shall be new and delivered as specified within the contract award. Vehicles shall be furnished with all interior, exterior trim and appointments listed by the manufacturer in printed specifications and literature as standard equipment. Vehicles shall also be equipped with any and all safety equipment required by the State of Arkansas and/or applicable Federal Regulations. Any upgrades and/or additional equipment necessitated by selection of any listed option by the ordering entity shall be included in the price, and no additional charge shall be made by the vendor.
- 3.2 Warranty - From date of delivery, each vehicle shall be accompanied by a warranty for a minimum of thirty-six (36) months or thirty six thousand (36,000) miles, whichever comes first. Warranty shall certify that the vehicle is of good material and workmanship and that the replacement of any part or parts that fails under normal use within the designated period, free of negligence or accident, will be promptly repaired or replaced at NO cost to the agency, institution, or other public body that purchased the vehicle.
- Specific Requirements See addenda 1 through 17 for specific requirements appropriate to each type 3.3 of vehicle listed herein.

#### 4. SAMPLING, INSPECTION, AND TEST PROCEDURES:

4.1 Responsibility for inspection - Unless otherwise specified, the successful contractor will be responsible for performing all inspections required herein. The Office of State Procurement reserves the right to make any and all inspections deemed necessary to insure compliance with these specifications.

#### 5. PREPARATION FOR DELIVERY:

Each vehicle shall be completely serviced, cleaned and thoroughly inspected by the successful contractor just prior to delivery to the purchasing entity. No dealer advertisement shall be on any vehicle purchased by the State of Arkansas.

#### PREDELIVERY REQUIREMENTS:

- a. Complete lubrication.
- b. Fill crankcase with oil.
- c. Adjustment of engine to proper operating conditions.
- d. Inflate tires to proper pressure.
- e. Careful check to assure perfect operation of all mechanical features.
- f. Front end alignment and wheels balanced.
- g. Cleaning of vehicle, if necessary, and removal of all unnecessary tags, stickers, papers, etc. Window price sticker shall not be removed.
- h. No dealer's insignia shall be affixed to automobile.
- i. A minimum 5 gallons of fuel in each vehicle.
- j. Delivery shall be during normal working hours, 8 A.M. 4 P.M. Monday Friday.
- k. License plate holder, front and rear.

AWARD NO: SP-09-0028 PAGE 53

## STANDARD SPECIFICATIONS FOR VANS, CARRYALLS AND UTILITY VEHICLES

ADDENDUM 1: TYPE VAA: Full Size One-Half (1/2) Ton Utility Van, 8-cylinder

#### A. Equipment:

- A.1 Standard equipment Each van shall be equipped with the following:
  - a. Air conditioning: factory installed.
  - b. Alternator: Heavy-duty, minimum 40 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - e. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - f. Bumpers: front and rear.
  - g. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - h. Doors: two (2) front, right and left with crank vertical windows, two (2) right side, to open in opposite direction or one (1) right sliding, and two (2) rear to open in opposite direction.
  - i. Engine: **Eight (8) cylinder** gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Glass: sides and rear cargo doors, manufacturer standard tinted glass in all windows.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - g. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Seats: two front, driver and passenger, manufacturer's standard colors and materials to coincide with vehicles exterior color.
  - t. Shock absorbers: Type recommended by manufacturer for vehicle as equipped.
  - u. Tires: Five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
- A.2 Optional equipment Purchaser may choose from the following:

- DO. Glass: sides and rear cargo doors, delete for credit.
- FI. Insulation: top, including full length headliner; sides, including trim panels, trim items may be dealer installed if equivalent in quality to standard type offered by manufacturer.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control (may be dealer installed of same manufacturer as vehicle) and tilt steering wheel.
- RA. Auxiliary Rear Air Condition Unit, rear heating, factory installed
- TO. Without air conditioning.

AWARD NO: SP-09-0028 PAGE 54

## ADDENDUM 2: TYPE VAB - Full Size Three-Quarter (3/4) Ton Utility Van, 8-cylinder

### A. Equipment:

- A.1 Standard Equipment Each van shall be equipped with the following:
  - a. Air Conditioning: factory installed.
  - b. Alternator: Heavy-Duty, minimum 40 amperes.
  - c. Anti-freeze: services to -29°C (-20°F) or lower.
  - d. Automatic Transmission: minimum of three (3) forward Speeds and one reverse.
  - e. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - f. Bumpers: front and rear.
  - g. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - h. Doors: two (2) front, right and left with cranked vertical opening windows, two (2) right side opposite opening, or one (1) right side sliding, and two (2) rear opposite opening.
  - i. Engine: Eight (8) cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Glass: sides and rear cargo doors, manufacturer standard tinted glass in all windows.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - q. Power Steering: factory installed.
  - t. Radio: factory installed in dash AM/FM.
  - u. Seats: two (2) front, driver and passenger.
  - v. Shock Absorbers: Type recommended by manufacturer for vehicle as equipped.
  - w. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
- A.2 Optional Equipment Purchaser may choose from the following:

#### **BD. 20 % Bio Diesel under OEM Warranty**

#### **DL. Daytime Running Lights**

DO. Glass: sides and rear cargo doors, delete for credit.

- FI. Insulation: top, including full length headliner; sides, including trim panels, trim items may be dealer installed if equivalent in quality to standard type offered by manufacturer.
- LS. Differential: limited slip, ratio as recommended by manufacturer.
- PO. Automatic Speed Control (may be dealer installed of same manufacturer as vehicle) and tilt steering wheel.

#### RA. Auxiliary Rear Air Condition Unit, rear heating, factory installed

TO. Without air conditioning

AWARD NO: SP-09-0028 PAGE 55

### ADDENDUM 3: TYPE VAC - Full Size One (1) Ton Utility Van, 8-cylinder

#### A. Equipment:

- A.1 Standard Equipment Each van shall be equipped with the following:
  - a. Air Conditioning: factory installed.
  - b. Alternator: Heavy-duty, minimum 60 amperes.
  - c. Anti-freeze: services to -29°C (-20°F) or lower.
  - d. Automatic Transmission: minimum of three (3) forward Speeds and one reverse.
  - e. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - f. Bumpers: front and rear.
  - g. Cooling System: heavy duty, including heavy duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - h. Doors: two (2) front, right and left with cranked vertical opening windows, two (2) right side opposite opening, or one (1) right side sliding, and two (2) rear opposite opening.
  - i. Engine: Eight (8) cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - j. Glass: manufacturer standard tinted glass in all windows.
  - k. Inside hood latch control.
  - I. License plate brackets: front and rear.
  - m. Mirrors: two (2) outside, low mount, right and left.
  - n. Operator's Manual.
  - o. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - p. Power Brakes: factory installed.
  - g. Power Steering: factory installed.
  - r. Radio: factory installed in dash AM/FM.
  - s. Seats: two (2) front, driver and passenger.
  - t. Shock Absorbers: Type recommended by manufacturer for vehicle as equipped.
  - u. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
- A.2 Optional Equipment Purchaser may choose from the following:
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - **DL. Daytime Running Lights**
  - DO. Glass: sides and rear cargo doors, delete for credit.
  - FI. Insulation: top, including full length headliner; sides, including trim panels, trim items maybe dealer installed if equivalent in quality to standard type offered by manufacturer.
  - LS. Differential: limited slip, ratio as recommended by manufacturer.
  - PO. Automatic Speed Control (may be dealer installed of same

manufacturer as vehicle) with tilt steering wheel.

RA. Auxiliary Rear Air Condition Unit, rear heating, factory installed

TO. Without air conditioning.

AWARD NO: SP-09-0028 PAGE 56

## ADDENDUM 4: TYPE VBA: Full Size One-Half (1/2) Ton Eight (8) Passenger Van

#### A. <u>Equipment:</u>

- A.1 Standard Equipment Each van shall be equipped with the following:
  - a. Air conditioning: factory installed, including factory installed insulation and heavy-duty alternator.
  - b. Alternator: minimum 60 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Doors: two (2) front; right and left, two (2) right side opposite opening, or one right side sliding, and two (2) rear opposite opening.

### j. Electronic Stability Control System (ex: StabiliTrak)

- k. Engine: a gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
- I. Glass: manufacturer standard tinted glass in all windows, with a minimum of three (3) windows capable of being opened.
- m. Inside hood latch control.
- n. Insulation: top, including full length headliner; sides, including trim panels, trim items may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
- o. License plate brackets: front and rear.
- p. Mirrors: two (2) outside, low mount, right and left.
- g. Operator's manual.
- r. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
- s. Power Windows and Power Door Locks: factory installed.
- t. Power Brakes: ABS factory installed.
- u. Power Steering: factory installed.
- v. Radio: factory installed in dash AM/FM.
- w. Seats: two (2) front, driver and passenger; and two (2) rear passenger, factory installed and removable, manufacturers standard materials, and color to coincide with vehicles exterior color.
- x. Shock absorbers: Type recommended by manufacturer for vehicle as equipped.
- y. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
- A.2 Optional Equipment: Purchaser may choose from the following:
  - CB. Gasoline Engine: 8-cylinder, a minimum of 280 CID.
  - **DL. Daytime Running Lights**
  - HC. Head-Curtain side impact air bags
  - LS. Differential: limited slip, ratio as recommended by manufacturer.
  - UO. Auxiliary, transmission oil cooler.

AWARD NO: SP-09-0028 PAGE 57

ADDENDUM 5: TYPE VGA: Three Quarter (3/4) Ton Eight (8) Passenger Van, 8-cylinder (larger van will not be accepted)

#### A. Equipment:

- A.1 Standard Equipment Each 3/4 ton vans shall be equipped with the following:
- a. Air conditioning with auxiliary rear unit, rear heating factory installed, and heavy duty alternator.
- b. Alternator: minimum 60 amperes.
- c. Anti-freeze: services to -29°C (-20°F) or lower.
- d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
- e. Automatic Transmission: minimum of three (3) forward Speeds and one reverse.
- f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
- g. Bumpers: front and rear.
- h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
- i. Doors: two (2) front; right and left, two (2) right side opposite opening, or one (1) right side sliding, and two (2) rear opposite opening.

## j. Electronic Stability Control System (ex: StabiliTrak)

- k. Engine: Eight (8) cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
- I. Glass: manufacturer standard tinted glass in all windows.
- m. Inside hood latch control.
- n. Insulation: top, including full length headliner; sides, including trim panels, trim items may be dealer installed if equivalent in quality to standard type offered by manufacturer.
- o. License plate brackets: front and rear.
- p. Mirrors: two (2) outside, low mount, right and left.
- q. Operator's manual.
- r. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
- s. Power Windows and Power Door Locks: factory installed.
- t. Power Brakes: ABS, factory installed.
- u. Power steering: factory installed.
- v. Radio: factory installed in dash AM/FM.
- w. Seats: two (2) front, driver and passenger, with a minimum of two (2) rear passenger seats factory installed and removable. Manufacturers' standard materials and colors to coincide with vehicles exterior color.
- x. Shock absorbers: Type recommended by manufacturer for vehicle as equipped.
- y. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
- A.2 Optional Equipment: Purchaser may choose from the following:
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - CC. Gasoline Engine: 8-cylinder, a minimum of a 325 CID.
  - **DL. Daytime Running Lights**
  - ET. Enhanced Technology Glass (ETG)
  - HC. Head-Curtain side impact air bags
  - HO. Seat (add one additional bench seat in rear of van).
  - LS. Differential: limited slip, ratio as recommended by manufacturer.
  - UO. Auxiliary, Transmission oil cooler.

AWARD NO: SP-09-0028 PAGE 58

ADDENDUM 6: TYPE VCA: One (1) Ton Twelve (12) Passenger Van

### A. <u>Equipment:</u>

- A.1 Standard Equipment Each van shall be equipped with the following:
  - a. Air conditioning with auxiliary rear unit, rear heating factory installed, and heavy-duty alternator.
  - b. Alternator: minimum 60 amperes.
  - c. Anti-freeze: services to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one reverse.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Doors: two (2) front, right and left, two (2) right side opposite opening, or one (1) right side sliding, and two (2) rear opposite opening.
  - j. Engine: Eight (8) cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - k. Glass: manufacturer standard tinted glass in all windows.
  - I. Inside hood latch control.
  - m. Insulation: top, including full length headliner; sides, including trim panels, trim items may be dealer installed if equivalent in quality to standard type offered by manufacturer.
  - n. License plate brackets: front and rear.
  - o. Mirrors: two (2) outside, low mount, right and left.
  - p. Operator's manual.
  - q. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - r. Power Windows and Power Door Locks: factory installed.
  - s. Power Brakes: **ABS**, factory installed.
  - t. Power steering: factory installed.
  - u. Radio: factory installed in dash AM/FM.
  - v. Seats: two (2) front, driver and passenger, and three (3) rear passenger factory installed and removable, manufacturer's standard materials and colors to coincide with vehicles exterior color.
  - w. Shock absorbers: Type recommended by manufacturer for vehicle as equipped.
  - x. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - y. Electronic Stability Control System (ex: StabiliTrak)
- A.2 Optional Equipment: Purchaser may choose from the following:
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - CC. Gasoline Engine: 8-cylinder, a minimum of a 325 CID.
  - **DL. Daytime Running Lights**
  - ET. Enhanced Technology Glass (ETG)
  - HC. Head-Curtain side impact air bags
  - LS. Differential: limited slip, ratio as recommended by manufacturer.
  - UO. Auxiliary, Transmission oil coolers.

AWARD NO: SP-09-0028 PAGE 59

ADDENDUM 7: TYPE VDA: One (1) Ton Fifteen (15) Passenger Van, 8-cylinder

### A. <u>Equipment:</u>

- A.1 Standard Equipment Each van shall be equipped with the following:
  - a. Air conditioning with auxiliary rear unit, rear heating: Factory, or dealer installed or O.E.M. warranted, and heavy-duty alternator.
  - b. Alternator: minimum 60 amperes.
  - c. Anti-freeze: service to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Doors: two (2) front; right and left, two (2) right side opposite opening, or one (1) right side sliding, and two (2) rear opposite opening.
  - j. Engine: a gasoline fueled eight (8)-cylinder engine of the type recommended by manufacturer for vehicle as equipped, a minimum of 325 CID.
  - k. Glass: manufacturer standard tinted glass in all windows.
  - I. Inside hood latch.
  - m. Insulation: top, including full length headliner; sides, including trim panels, trim items may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
  - n. License plate brackets: front and rear.
  - o. Mirrors: two (2) outside, low mount, right and left.
  - p. Operator's manual.
  - q. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - r. Power windows and power door locks: factory installed
  - s. Power Brakes: ABS, factory installed.
  - t. Power steering: factory installed.
  - u. Radio: factory installed in dash AM/FM.
  - v. Seats: two (2) front, driver and passenger, and four (4) rear passenger factory installed and removable, manufacturer's standard materials and colors to coincide with vehicles exterior color.
  - w. Shock absorbers: Type recommended by manufacturer for vehicle as equipped.
  - x. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - y. Electronic Stability Control System (ex: StabiliTrak)
- A.2 Optional Equipment Purchaser may choose from the following:
  - **BD. 20 % Bio Diesel under OEM Warranty**
  - CB. Gasoline Engine: 8-cylinder, a minimum of a 280 CID
  - **DL. Daytime Running Lights**
  - ET. Enhanced Technology Glass (ETG)
  - HC. Head-Curtain side impact air bags
  - LS. Differential: limited slip, ratio as recommended by manufacturer.
  - UO. Auxiliary, transmission oil coolers.
  - WW. Cloth bench seats & carpet.

AWARD NO: SP-09-0028 PAGE 60

ADDENDUM 8: TYPE VEA: Compact Utility Mini-Van, 4-cylinder (Larger Van Will Not Be Accepted)

### A. Equipment:

- A.1 Standard Equipment Each van shall be equipped with the following:
  - a. Air conditioning: factory installed, including insulation which may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer and heavy-duty alternator.
  - b. Alternator: type recommended by manufacturer for vehicle as equipped.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, and type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - j. Doors: two (2) front, right and left, two (2) rear, right and left and of the type recommended by manufacturer for vehicle as equipped.
  - k. Engine: **Four (4) cylinder** gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - I. Glass: Manufacturer standard tinted glass in all windows.
  - m. Inside hood latch control.
  - n. License plate brackets: front and rear.
  - o. Mirrors: two (2) outside, low mount, right and left.
  - p. Operator's manual.
  - q. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - r. Power brakes: factory installed.
  - s. Power steering: factory installed.
  - t. Radio: factory installed in dash AM/FM.
  - u. Seats: two (2) front, driver and passenger, manufacturer's standard type.
  - v. Suspension: Type recommended by manufacturer for vehicle as equipped.
  - w. Tires: four (4) radial, tubeless, type recommended by manufacturer for vehicle as equipped, and one (1) mounted spare tire with wheel, either "space saver" or full size.
- A.2 Optional Equipment Purchaser may choose from the following:

- JO. Glass: manufacturer standard tinted rear cargo door(s).
- TO. Without air conditioning.

AWARD NO: SP-09-0028 PAGE 61

ADDENDUM 9: TYPE VFA: Compact (7) Passenger Mini-Van, 6-cylinder (Larger Van Will Not Be Accepted)

#### A. Equipment:

- A.1 Standard Equipment Each van shall be equipped with the following:
  - a. Air conditioning: factory installed.
  - b. Alternator: heavy duty, and type recommended by manufacturer for vehicle as equipped.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free, and type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - j. Doors: two (2) front, two (2) rear, type recommended by manufacturer for vehicle as equipped
  - k. Engine: 6-cylinder gasoline fueled, and type recommended by manufacturer as being capable of handling a fully loaded passenger van as equipped.
  - I. Glass: manufacturer standard tinted glass in all windows, with windows capable of being opened in at least one (1) location on each side to the rear of driver area.
  - m. Inside hood latch control.
  - n. Insulation: top, including full length headliner; sides, including trim panels; may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
  - o. License plate brackets: front and rear.
  - p. Mirrors: two outside. low mount, right and left.
  - g. Operator's manual.
  - r. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - s. Power Windows and Power Door Locks: factory installed.
  - t. Power Brakes: factory installed.
  - u. Power Steering: factory installed.
  - v. Radio: factory installed in dash AM/FM.
  - w. Seats: manufacturer's standard seven (7) passenger (minimum) seating arrangement, factory installed and removable. Manufacturer's standard materials, and color to coincide with vehicles exterior color.
  - x. Suspension: type recommended by manufacturer for vehicle as equipped.
  - y. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - A.2 Optional Equipment Purchaser may choose from the following:

AWARD NO: SP-09-0028 PAGE 62

#### ADDENDUM 10: TYPE PHA: Compact 2 WD Utility Vehicle, 4-cylinder

#### A. Equipment:

- A.1 Standard Equipment Each compact two wheel drive (2WD) special purpose vehicle shall be equipped with the following, as standard equipment listed by manufacturer, as required by this specification.
  - a. Air conditioning: all weather, factory installed.
  - b. Alternator: minimum of 40 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower, and vehicle to be completely winterized.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - j. Doors: Four (4): Front; right and left. Rear; right and left.
  - k. Engine: **Four (4) cylinder** gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - I. Floor Mats: individual front and rear, color to coincide with interior.
  - m. Glass: manufacturer standard tinted glass in all windows.
  - n. Inside hood latch control.
  - o. Insulation: top, including full length headliner; sides, including trim panels; may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
  - p. License plate brackets: front and rear.
  - q. Mirrors: exterior, low mount (below eye level type), right and left, and one (1) interior.
  - r. Operator's manual.
  - s. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - t. Power Windows and Power Door Locks: factory installed.
  - u. Power brakes: factory installed.
  - v. Power steering: factory installed.
  - w. Radio: factory installed in dash AM/FM.
  - x. Seats: Bucket or split bench in front, fold down bench type in rear and seat belts for all seats.

Manufacturers' standard materials and color to coincide with exterior color.

- y. Shock Absorbers: Type recommended by manufacturer for vehicle as equipped.
- z. Tires: Four (4) according to manufacturer's factory standard with one (1) spare.
- aa. Windshield washer: with two (2) Speed wipers.
- bb. Fuel tank: approximately 16 gallon capacity or more.
- cc. Lamp: interior dome with door courtesy warning feature.
- dd. Stabilizer equipment: front.
- ee. Storage box: instrument panel area.
- ff. Trailer package: to include external oil and transmission cooler.
- A.2 Optional Equipment Purchaser may choose from the following:

#### **DL. Daytime Running Lights**

### LR Low Range Gears for off-road use

XM. Hitch, Class II, frame attached. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 63

#### ADDENDUM 11: TYPE PHB: Compact 4 WD Utility Vehicle, 6-cylinder

#### A. Equipment:

- A.1 Standard Equipment Each compact four wheel drive (4WD) special purpose vehicle shall be equipped with the following, as standard equipment listed by manufacturer, as required by this specification.
  - a. Air conditioning: all weather, factory installed.
  - b. Alternator: minimum of 95 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower, and vehicle to be completely winterized.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - j. Doors, Four (4): Front; right and left. Rear, right and left
  - k. Engine: Six (6) cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - I. Floor Mats: individual front and rear, color to coincide with interior.
  - m. Glass: manufacturer standard tinted glass in all windows.
  - n. Inside hood latch control.
  - o. Insulation: top, including full length headliner; sides, including trim panels; may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
  - p. License plate brackets: front and rear.
  - q. Mirrors: exterior, low mount (below eye level type), right and left, and one (1) interior.
  - r. Operator's manual.
  - s. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - t. Power Windows and Power Door Locks: factory installed.
  - u. Power brakes: factory installed.
  - v. Power steering: factory installed.
  - w. Radio: factory installed in dash AM/FM.
  - x. Seats: Bucket or split bench in front, fold down bench type in rear, and seat belts for all seats; manufacturer's standard materials and color to coincide with exterior color.
  - v. Shock Absorbers: Type recommended by manufacturer for vehicle as equipped.
  - z. Tires: four (4) according to manufacturer's factory standard with one (1) spare.
  - aa. Windshield washer: with two (2) Speed wipers.
  - bb. Fuel tank: approximately 16-gallon capacity or more.
  - cc. Lamp: interior dome with door courtesy warning feature.
  - dd. Stabilizer equipment: front.
  - ee. Storage box: instrument panel area.
  - ff. Trailering package: to include external oil and transmission cooler.
- A.2 Optional Equipment Purchaser may choose from the following:

### **DL. Daytime Running Lights**

- KO. Skid plate.
- LO. Special Equipment Package (to include steel wheels, rear window wiper and defroster). (not a police pkg.)

## LR Low Range Gears for off road terrain.

XO. Hitch, Class III, frame attached. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 64

### ADDENDUM 12: TYPE PHC: Compact AWD Utility Vehicle, 6-cylinder

#### A. Equipment:

- A.1 Standard Equipment Each compact All Wheel Drive (AWD) special purpose vehicle shall be equipped with the following as standard equipment listed by manufacturer, as required by this specification.
  - a. Air Conditioning: all weather, factory installed.
  - b. Alternator: minimum of 95 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower. Vehicle to be completely winterized.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: min. of three forward and one reverse speed.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - **j. Doors, Four (4): Front: right and left. Rear: right and left;** type recommended by manufacturer for vehicle as equipped.
  - k. Engine: **Six (6) cylinder** gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.

#### I. Fuel Tank: approximately 19-gallon capacity or more

- m. Glass: manufacturer standard tinted glass in all windows.
- n. Inside hood latch control.
- o. Insulation: top, including full length headliner; sides, including trim panels, trim items may be dealer installed if equivalent in quality to type offered by vehicle manufacturer.

#### p. Lamp: interior dome with door courtesy warning feature

- q. License plate brackets: front and rear.
- r. Mirrors: two (2) outside, low mount, right and left. One (1) interior.
- s. Operator's Manual.
- t. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
- u. Power Windows and Power Door Locks: factory installed.
- v. Power Brakes: factory installed.
- w. Power Steering: factory installed.
- x. Radio: factory installed in dash AM/FM.
- y. Seats: **Bucket or split bench in front, fold down bench type in rear,** manufacturer's standard materials, with color to coincide with vehicles exterior color.
- z. Shock Absorbers: Manufacturer's recommendation for vehicle as equipped.

### aa. Stabilizer Equipment: front

- bb. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
- cc. Trailering Package: to include external oil and transmission cooler.
- dd. Windshield Washer: with two (2) speed wipers.
- A.2 Optional Equipment: Purchaser may choose from the following:

- KO. Skid Plate
- LO. Special Equipment Package to include steel wheels, rear window wiper and defroster (not a police package).
- XO. Hitch, Class III, frame attached. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 65

#### ADDENDUM 13: TYPE PIA: Midsize 2 WD Utility Vehicle, 6-cylinder

### A. <u>Equipment:</u>

- A.1 Standard Equipment Each midsize two wheel drive (2WD) special purpose vehicle shall be equipped with the following, as standard equipment listed by manufacturer, as required by this specification.
  - a. Air conditioning: all weather, factory installed.
  - b. Alternator: minimum of 40 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower, and vehicle to be completely winterized.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - j. Doors: Four (4): Front; right and left. Rear, right and left.
  - k. Engine: Six (6) cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - I. Floor Mats: individual front and rear, color to coincide with interior.
  - m. Glass: manufacturer standard tinted glass in all windows.
  - n. Inside hood latch control.
  - o. Insulation: top, including full length headliner; sides, including trim panels; may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
  - p. License plate brackets: front and rear.
  - q. Mirrors: exterior, low mount (below eye level type), right and left, and one (1) interior.
  - r. Operator's manual.
  - s. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - t. Power Windows and Power Door Locks: factory installed.
  - u. Power brakes: factory installed.
  - v. Power steering: factory installed.
  - w. Radio: factory installed in dash AM/FM.
  - x. Seats: Bucket or split bench in front, fold down bench type in rear and seat belts for all seats. Manufacturers' standard materials and color to coincide with exterior color.
  - y. Shock Absorbers: Type recommended by manufacturer for vehicle as equipped.
  - z. Tires: Four (4) according to manufacturer's factory standard with one (1) spare.
  - aa. Windshield washer: with two (2) Speed wipers.
  - bb. Fuel Tank: approximately 17 gallon capacity or more.
  - cc. Lamp: interior dome with door courtesy warning feature.
  - dd. Stabilizer Equipment: front.
  - ee. Storage box: instrument panel area.
  - ff. Trailer Package: to include external oil and transmission cooler.
- A.2 Optional Equipment Purchaser may choose from the following:

- KO. Skid Plate
- LO. Special Equipment Package to include steel wheels, rear window wiper and defroster (not a police package).
- XO. Hitch, Class III, frame attached. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 66

#### ADDENDUM 14: TYPE PIB: Midsize 4 WD Utility Vehicle, 6-cylinder

#### A. <u>Equipment:</u>

- A.1 Standard Equipment Each midsize four wheel drive (4WD) special purpose vehicle shall be equipped with the following as standard equipment listed by manufacturer, as required by this specification.
  - a. Air conditioning: all weather, factory installed.
  - b. Alternator: minimum of 40 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower, and vehicle to be completely winterized.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - j. Doors: Four (4): Front; right and left. Rear, right and left; type recommended by manufacturer for vehicle as equipped.
  - k. Engine: 6-cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - I. Floor Mats: individual front and rear, color to coincide with interior.
  - m. Glass: manufacturer standard tinted glass in all windows.
  - n. Inside hood latch control.
  - o. Insulation: top, including full length headliner; sides, including trim panels; may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
  - p. License plate brackets: front and rear.
  - q. Mirrors: exterior, low mount (below eye level type), right and left, and one (1) interior.
  - r. Operator's manual.
  - s. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - t. Power Windows and Power Door Locks: factory installed.
  - u. Power brakes: factory installed.
  - v. Power steering: factory installed.
  - w. Radio: factory installed in dash AM/FM.
  - x. Seats: Bucket or split bench in front, fold down bench type in rear and seat belts for all seats. Manufacturers' standard materials and color to coincide with exterior color.
  - y. Shock Absorbers: Type recommended by manufacturer for vehicle as equipped.
  - z. Tires: Four (4) according to manufacturer's factory standard with one (1) spare.
  - aa. Windshield washer: with two (2) Speed wipers.
  - bb. Fuel Tank: approximately 17 gallon capacity or more.
  - cc. Lamp: interior dome with door courtesy warning feature.
  - dd. Stabilizer equipment: front.
  - ee. Storage box: instrument panel area.
  - ff. Trailer package: to include external oil and transmission cooler.
- A.2 Optional Equipment Purchaser may choose from the following:

- KO. Skid Plate
- LO. Special Equipment Package to include steel wheels, rear window wiper and defroster (not a police package).
- XO. Hitch, Class III, frame attached. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 67

### ADDENDUM 15: TYPE PSA: Full-Size 2 WD Utility Vehicle, 8-cylinder

#### A. Equipment:

- A.1 Standard Equipment Each full-size two wheel drive (2WD) special purpose vehicle shall be equipped with the following, as standard equipment listed by manufacturer, as required by this specification.
  - a. Air conditioning: all weather, factory installed.
  - b. Alternator: minimum of 95 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower, and vehicle to be completely winterized.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling system: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - j. Doors, Four (4): Front; right and left. Rear; right and left.; type recommended by manufacturer for vehicle as equipped.
  - k. Engine: Eight (8) cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - I. Floor Mats: individual front and rear, color to coincide with interior.
  - m. Glass: manufacturer standard tinted glass in all windows.
  - n. Inside hood latch control.
  - o. Insulation: top, including full length headliner; sides, including trim panels; may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
  - p. License plate brackets: front and rear.
  - q. Mirrors: exterior, low mount (below eye level type), right and left, and one (1) interior.
  - r. Operator's manual.
  - s. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - t. Power Windows and Power Door Locks: factory installed.
  - u. Power Brakes: factory installed.
  - v. Power Steering: factory installed.
  - w. Radio: factory installed in dash AM/FM.
  - x. Seats: Front: Bucket or split bench, 2<sup>nd</sup> Row: Fold Down Bench Type, 3<sup>rd</sup> Row: Fold- Flat to the Floor Type, and seat belts for all seats; manufacturer's standard materials and color to coincide with exterior color.
  - y. Shock Absorbers: Type recommended by manufacturer for vehicle as equipped.
  - z. Tires: four (4) according to manufacturer's factory standard with one (1) spare.
  - aa. Windshield Washer: with two (2) Speed wipers.
  - bb. Fuel Tank: approximately 25-gallon capacity or more.
  - cc. Lamp: interior dome with door courtesy warning feature.
  - dd. Stabilizer Equipment: front, and rear.
  - ee. Storage Box: instrument panel area.
  - ff. Trailering Package: to include oil and transmission cooler.
  - gg. Wheelbase: 115" minimum.
- A.2 Optional Equipment Purchaser may choose from the following:

- HS. Heavy service package, including heavy-duty alternator, battery, suspension and maximum engine/transmission cooling.
- KO. Skid Plate
- LO. Special Equipment Package to include steel wheels, rear window wiper and defroster. (not a police pkg.)
- LS. Limited slip rear end.
- XO. Hitch, Class III, frame attached. Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 68

## ADDENDUM 16: TYPE PSB: Full-Size 4 WD Utility Vehicle, 8-cylinder

#### A. Equipment:

- A.1 Standard Equipment Each full-size four wheel drive (4WD) special purpose vehicle shall be equipped with the following, as standard equipment listed by manufacturer, as required by this specification.
  - a. Air Conditioning: all weather, factory installed.
  - b. Alternator: minimum of 95 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower, and vehicle to be completely winterized.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: minimum of three (3) forward Speeds and one (1) reverse.
  - f. Battery: maintenance free; type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Differential: ratio as recommended by manufacturer.
  - j. Doors, Four (4): Front; right and left. Rear; right and left. type recommended by manufacturer for vehicle as equipped.
  - k. Engine: Eight (8) cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - I. Floor Mats: individual front and rear, color to coincide with interior.
  - m. Glass: manufacturer standard tinted glass in all windows.
  - n. Inside hood latch control.
  - o. Insulation: top, including full length headliner; sides, including trim panels; may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer.
  - p. License plate brackets: front and rear.
  - q. Mirrors: exterior, low mount (below eye level type), right and left, and one (1) interior.
  - r. Operator's Manual.
  - s. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - t. Power Windows and Power Door Locks: factory installed.
  - u. Power Brakes: factory installed.
  - v. Power Steering: factory installed.
  - w. Radio: factory installed in dash AM/FM.
  - x. Seats: Front: Bucket or split bench, 2<sup>nd</sup> Row: Fold Down Bench Type, 3<sup>rd</sup> Row: Fold Flat to the Floor Type and seat belts for all seats; manufacturer's standard materials and color to coincide with exterior color.
  - y. Shock Absorbers: Type recommended by manufacturer for vehicle as equipped.
  - z. Tires: four (4) according to manufacturer's factory standard with one (1) spare.
  - aa. Windshield Washer: with two (2) Speed wipers.
  - bb. Fuel Tank: approximately 25 gallon capacity or more.
  - cc. Lamp: interior dome with door courtesy warning feature.
  - dd. Stabilizer Equipment: front, and rear.
  - ee. Storage Box: instrument panel area.
  - ff. Trailering Package: to include oil and transmission cooler.
  - gg. Wheelbase: 115" minimum.
- A.2 Optional Equipment Purchaser may choose from the following:

- HS. Heavy service package, including heavy duty alternator, battery, suspension and maximum engine/transmission cooling.
- KO. Skid Plate (s)
- LO. Special Equipment Package to include steel wheels, rear window wiper and defroster (not a police pkg.)
- LS. Limited slip rear end.
- XO. Hitch, Class III, frame attached, Must be dealer or manufacturer installed. Insert bar and ball not included.

AWARD NO: SP-09-0028 PAGE 69

#### ADDENDUM 17: TYPE PMA: Eight (8) Passenger Carryall

#### A. Equipment:

- A.1 Standard Equipment Each four (4) door carryall with rear entry access shall be equipped with the following standard equipment listed by manufacturer, as required by this specification.
  - a. Air Conditioning: factory installed, including factory installed insulation and heavy-duty alternator.
  - b. Alternator: minimum of 100 amperes.
  - c. Anti-freeze: serviced to -29°C (-20°F) or lower.
  - d. Automatic Speed Control (may be dealer installed, but of same manufacturer as vehicle) and tilt steering wheel.
  - e. Automatic Transmission: min. of three forward and one reverse Speed.
  - f. Battery: maintenance free, type recommended by manufacturer for vehicle as equipped.
  - g. Bumpers: front and rear.
  - h. Cooling System: heavy-duty, including heavy-duty radiator, heavy-duty fan, and factory installed coolant recovery system.
  - i. Doors: Four (4) doors with lift gate, tail gate or panel door(s) type rear entry.
  - j. Engine: 8-cylinder gasoline fueled engine of the type recommended by manufacturer for vehicle as equipped.
  - k. Floor Mats: individual front and rear, color to coincide with interior.
  - I. Glass: manufacturer standard tinted glass in all windows, with a minimum of four (4) windows capable of being opened.
  - m Inside hood latch control.
  - n. Insulation: top, including full length headliner; sides, including trim panels, trim items may be dealer installed if equivalent in quality to type offered by vehicle manufacturer.
  - o. License plate brackets: front and rear.
  - p. Mirrors: two (2) outside, low mount, right and left.
  - q. Operator's Manual.
  - r. Paint: one (1) standard exterior color selected from manufacturer's standard list and specified by ordering entity.
  - s. Power Windows and Power Door Locks: factory installed.
  - t. Power Brakes: factory installed.
  - u. Power Steering: factory installed.
  - v. Radio: factory installed in dash AM/FM.
  - w. Seats: Eight (8) passenger, with factory installed 2nd row folding center and a 3rd row detachable rear seat, from manufacturer's standard materials, with color to coincide with vehicles exterior color.
  - x. Shock Absorbers: Manufacturer's recommendation for vehicle as equipped.
  - y. Tires: five (5) radial, tubeless, type recommended by manufacturer for vehicle as equipped.
  - z. Wheelbase: 130" minimum
- A.2 Optional Equipment: Purchaser may choose from the following:
  - AO. Four wheel drive (with standard equipment and buyers' choice of options as listed).

- LS. Differential: limited slip, ratio as recommended by manufacturer.
- NO. Bucket or Captain Seats with center console. (includes option WW)
- WO. Factory installed rear air conditioning system.
- XO. Hitch, Class III, frame attached. Must be dealer or manufacturer installed. Insert bar and ball not included. A minimum rear axle ratio of 3.31 is needed for option XO.
- WW. Cloth 2<sup>nd</sup> and 3<sup>rd</sup> row seats, includes carpet and carpeted floor mats.